

CRANE ARMS TYPE KT / KTH



A crane arm increases the reach of the forklift truck

- steel construction
- secured by chain to prevent slipping

Extensible constructions

- extension arm is positioned inside the shell and can be extended in 8 steps to reach full length; locked in position using the pin provided
- 14 possible positions; 2 swivel hooks

KT

- rigid construction

KTH

- variable working height, can be fixed in each of the positions using the pin provided
- a choice of 3 angles: 15°, 30° or 45°

Fixed-length constructions

- 5 possible positions; 1 swivel hook

KT-K

- rigid construction

KTH-K

- variable working height, can be fixed in each of the positions using the pin provided
- a choice of 3 angles: 15°, 30° or 45°

Accessories

- hydraulic extension function (max. 1000 mm, for KT and KTH)



Hydraulic extension function (KTH)

KTH extended and at an elevated working height




KT-K



KTH-K at an elevated working height

Fork sleeve inside dimensions in mm



| | A | B | C |
|-------------------|-----|-----|----|
| KT 2,5/KT-K 2,5 | 106 | 184 | 84 |
| KT 5,0/KT-K 5,0 | 116 | 184 | 84 |
| KTH 2,5/KTH-K 2,5 | 156 | 184 | 84 |
| KTH 5,0/KTH-K 5,0 | 166 | 184 | 84 |

| | Position | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | Dimensions lwxhxh | Weight |
|-----------|---------------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|-------------------|--------------------|
| | Distance in mm | 710 | 1000 | 1290 | 1590 | 1870 | 2055 | 2255 | 2455 | 2655 | 2855 | 3055 | 3255 | 3455 | 3655 | in mm | paint./galv. in kg |
| KT-K 2,5 | Load capacity in kg | 2500 | 2500 | 2500 | 1800 | 1400 | - | - | - | - | - | - | - | - | - | 2000 x 490 x 480 | 135 / 145 |
| KT 2,5 | Load capacity in kg | 2500 | 2500 | 2500 | 1800 | 1400 | 1200 | 1050 | 950 | 850 | 770 | 700 | 650 | 600 | 560 | 2160 x 490 x 480 | 175 / 188 |
| KT-K 5,0 | Load capacity in kg | 5000 | 3550 | 2750 | 2250 | 1950 | - | - | - | - | - | - | - | - | - | 2000 x 500 x 520 | 160 / 172 |
| KT 5,0 | Load capacity in kg | 5000 | 3550 | 2750 | 2250 | 1950 | 1700 | 1550 | 1400 | 1300 | 1200 | 1150 | 1050 | 1000 | 950 | 2160 x 500 x 520 | 210 / 226 |
| | Distance in mm | 695 | 990 | 1285 | 1580 | 1825 | 2090 | 2290 | 2490 | 2690 | 2890 | 3090 | 3290 | 3490 | 3690 | | |
| KTH-K 2,5 | Load capacity in kg | 2500 | 2500 | 2500 | 1800 | 1400 | - | - | - | - | - | - | - | - | - | 2050 x 540 x 560 | 160 / 172 |
| KTH 2,5 | Load capacity in kg | 2500 | 2500 | 2500 | 1800 | 1400 | 1200 | 1050 | 950 | 850 | 770 | 700 | 650 | 600 | 560 | 2200 x 540 x 560 | 203 / 218 |
| KTH-K 5,0 | Load capacity in kg | 5000 | 3550 | 2750 | 2250 | 1950 | - | - | - | - | - | - | - | - | - | 2050 x 550 x 600 | 184 / 198 |
| KTH 5,0 | Load capacity in kg | 5000 | 3550 | 2750 | 2250 | 1950 | 1700 | 1550 | 1400 | 1300 | 1200 | 1150 | 1050 | 1000 | 950 | 2200 x 550 x 600 | 235 / 253 |

Remember to check the load capacity of the forklift truck in question!

| | | | | | | |
|---------|----------|----------|----------|----------|----------|--------------------|
| Finish: | RAL 2000 | RAL 3000 | RAL 5012 | RAL 6011 | RAL 7005 | hot-dip galvanized |
|---------|----------|----------|----------|----------|----------|--------------------|