

# ACCESS SAFETY PLATFORM TYPE MB-I




MB-I with straddle stacker



MB-I secured to the forklift by chain



Safety mechanism for a straddle stacker



Secured by bolt to prevent slipping from the forklift truck



PPE anchor point (personal protective equipment)

|      |        | Dimensions<br>in mm (l x w x h) | Floor area<br>in mm | Total permitted<br>weight in kg | Weight<br>in kg | Fork sleeve inside dimensions in mm |     |    |
|------|--------|---------------------------------|---------------------|---------------------------------|-----------------|-------------------------------------|-----|----|
|      |        |                                 |                     |                                 |                 | A                                   | B   | C  |
| MB-I | MB-I/A | 775 x 800 x 2050                | 645 x 650           | 180                             | 60              | 165                                 | 210 | 85 |

## Access Safety Platform for straddle stackers or forklifts that ensure safety for repairs and maintenance work at height

- number of persons permitted: 1
- "DGUV" compliant (German Use of Work Equipment Directive) and approved by the German Association for Technical Inspection "TÜV")
- fork sleeves
- safety mechanism to prevent slippage for both straddle stackers and forklift trucks
- galvanized tool deposit
- 4 support legs
- finish: painted **RAL 2000**

### Types available

#### MB-I

- as described above


#### MB-I/A

- PPE anchor point (personal protective equipment)
- Accessories**
- PPE anchor point (personal protective equipment) (MB-I)



TÜV Austria

Fork sleeve inside dimensions in mm



# ACCESS SAFETY PLATFORM TYPE MB-ST



MB-ST



MB-ST/T

|           |  | Dimensions<br>in mm (l x w x h) | Floor area<br>in mm | Total permitted<br>weight in kg | Weight<br>in kg (painted/galv.) | Fork sleeve inside dimensions in mm |     |    |
|-----------|--|---------------------------------|---------------------|---------------------------------|---------------------------------|-------------------------------------|-----|----|
|           |  |                                 |                     |                                 |                                 | A                                   | B   | C  |
| MB-ST     |  | 1040 x 1335 x 1890              | 800 x 1200          | 300                             | 130 / 142                       | 600                                 | 200 | 80 |
| MB-ST-L   |  | 1300 x 930 x 1890               | 1200 x 800          | 300                             | 136 / 146                       | 160                                 | 200 | 80 |
| MB-ST/T   |  | 1050 x 1415 x 1890              | 800 x 1200          | 300                             | 140 / 151                       | 600                                 | 200 | 80 |
| MB-ST/T-L |  | 930 x 1375 x 1890               | 1200 x 800          | 300                             | 136 / 146                       | 160                                 | 200 | 80 |

## For work at height such as storage and retrieval operations or stocktaking

- number of persons permitted: 1
- fork sleeves with safety mechanism to prevent slipping
- galvanized tool deposit

### Types available

#### MB-ST

- two-hand control switch, flash light, cable retractor with 8 m cable, plug, socket and spare plug
- picked up broadside by a forklift truck

#### MB-ST-L

- like the MB-ST, but picked up lengthwise (narrow base)

#### MB-ST/T

- similar to type MB-ST, but with circuit breaker for the door
- all-round safety mesh

#### MB-ST/T-L

- like the MB-ST/T but picked up lengthwise (narrow base)

### Accessories

- PPE anchor point (personal protective equipment)

Finish: **RAL 2000** hot-dip galvanized