

VORAS




①

①








②






18 cm

70 cm





REF.	FA 20 303 02
LG. 	2.50 m
KG	140 KG
CE	EN 360:2002
MAT. 	PVC PA & PES 50 mm
	 FA 50 207 55 / FA 50 202 17
	x1
R(kN)	15 kN
	NO
	1.70 KG

<p>LG. </p> <p>Longueur Poids maxi utilisateur Length Max. user weight Longitud Peso máximo del usuario Lunghezza Peso Max. dell'utente Länge Höchstgewicht des Benutzers</p>	<p>MAT. </p> <p>Matière carter / sangle Material of casing / webbing Material cárter / correa Material dei carter / Cinghia Material Gehäuse / Gurt</p>	<p></p> <p>Matière connecteur haut / connecteur bas Material of top connector / bottom connector Material conector alto / conector bajo Materiale connettore alto / connettore basso Material oberes / unteres Verbindungselement</p>
<p></p> <p>Nombre d'émerillons Number of swivels Cantidad de eslabones giratorios Numero di tornichetti Anzahl der Wirbel</p>	<p></p> <p>Homologué pour le travail à proximité d'arêtes vives Approved for work near sharp edges Homologado para trabajo cerca de aristas vivas Omologato per lavoro in prossimità di spigoli vivi Zugelassen für Arbeiten in der Nähe scharfer Kanten</p>	