



## Cable blocks 6 - 15 metre

**Model: CMHCR250v06-2** (192066967)  
6 metre fall arrest block with 4mm diameter cable.  
Fitted as standard with fall indicator in connector.  
WLL 120kg. Unit weight 4kg

**Model: CMHCR250v10-2** (192066968)  
10 metre fall arrest block with 4mm diameter cable.  
Fitted as standard with fall indicator in connector.  
WLL 120kg. Unit weight 4.2kg

**Model: CMHCR250v12-2** (192066972)  
12 metre fall arrest block with 4mm diameter cable.  
Fitted as standard with fall indicator in connector.  
WLL 120kg. Unit weight 4.7kg

**Model: CMHCR250v15-2** (192066973)  
15 metre fall arrest block with 4mm diameter cable.  
Fitted as standard with fall indicator in connector.  
WLL 120kg. Unit weight 4.9kg



## Retrieval block 25 metre

**Model: CMHCRW30025** (Article: 192040308)  
25 metre fall arrest / retrieval block for fall arrest and rescue with 4.7mm diameter galvanised steel cable. Max. rated load 100kgs, minimum rated load 50kgs. For lifting & lowering personnel only. Conforms to BS EN360, BS EN1496 Class B.



## Cable blocks 20 - 25 metre

**Model: CMHCR30020** (Article: N37320020)  
20 metre fall arrest block with 4mm diameter cable.  
Fitted as standard with fall indicator in connector.  
WLL 120kg. Unit weight 11.25kg.  
*\*Replacement rope 20m x 4mm N4300007540 £63.27*

**Model: CMHCR30025** (Article: N37320025)  
25 metre fall arrest block with 4mm diameter cable.  
Fitted as standard with fall indicator in connector.  
WLL 120kg. Unit weight 11.5kg.  
*\*Replacement rope 25m x 4mm N4300007541 £68.37*



## Webbing blocks

**Model: CMHWR100-06** (Article: N4300013778)  
6 metre fall arrest block with 17mm wide webbing polyester - Kevlar fibres. Fitted as standard with fall indicator in connector.  
WLL 120kg. Unit weight 1.7kgs.

**Model: CMHAH210** (Article: N37320035)  
2.25 metre mini retractor with 45mm wide webbing.  
Fitted as standard with fall indicator in connector.  
WLL 120kg. Unit weight 1.2kg.

All fall arrest blocks conform to BS EN360.