

Yalelift 360[®] MK III 'INTEGRAL' TROLLEY HOISTS

Hand chain hoist with integrated push or geared travel trolley

Capacities: 500 - 20000kg

The combination of the Yalelift 360[°] with a low headroom manual trolley provides even more flexibility in the application of the Yalelift 360[°].

Features include:

- All units of this series up to a capacity of 3000 kg are provided with single chain fall and the min. headroom (Dim. A) has been further reduced. Ideal for applications with low ceilings and limited headroom.
- The proven and almost stepless adjustment system allows quick and easy assembly of the trolley.
- Trolleys up to 5000kg are offered for two beam ranges. Range A for a flange width up to 180mm is standard and covers approx. 80 % of all requirements. Conversion to range B for beam width up to 300mm can be easily accomplished.
- The trolley wheels are designed for a max. beam profile incline of 14 % (DIN 1025 - part 1), excellent rolling features are guaranteed by prelubricated, encapsulated ball bearings.
- Anti-drop and anti-tilt devices as standard.

Options:

- Overload prevention device.
- Chain container.
- Rubber buffers (shown in photograph on the right available as optional extra).
- Explosion proof version (see page 18-19).
- Beam locking device to secure the unloaded trolley in a fixed position on the beam (park position e.g. on ships). Available up to a capacity of 5000 kg.



Yalelift ITP INTEGRAL PUSH TROLLEY HOISTS

Model	Capacity (WLL) kg	Falls of load chain	Lifting height mtr	Curve radius min. mtr	Beam width mm	Closed height mm	Weight @ 3mtr HOL kg
YLITP A 500	500	1	3	0.9	50 - 180	245	20
YLITP B 500	500	1	3	0.9	180 - 300	245	21
YLITP A 1000	1000	1	3	0.9	50 - 180	272	27
YLITP B 1000	1000	1	3	0.9	180 - 300	272	29
YLITP A 2000	2000	1	3	1.15	58 - 180	323	44
YLITP B 2000	2000	1	3	1.15	180 - 300	323	46
YLITP A 3000	3000	1	3	1.5	74 - 180	382	77
YLITP B 3000	3000	1	3	1.4	180 - 300	382	79
YLITP A 5000	5000	2	3	2.0	98 - 180	550	125
YLITP B 5000	5000	2	3	1.8	180 - 300	550	129

*Additional heights of lift are sold as complete metres only.

Yalelift ITG INTEGRAL GEARED TROLLEY HOISTS

Model	Capacity (WLL) kg	Falls of load chain	Lifting height mtr	Curve radius min. mtr	Beam width mm	Closed height mm	Weight @ 3mtr HOL kg
YLITG A 500	500	1	3	0.9	50 - 180	245	24
YLITG B 500	500	1	3	0.9	180 - 300	245	25
YLITG A 1000	1000	1	3	0.9	50 - 180	272	34
YLITG B 1000	1000	1	3	0.9	180 - 300	272	33
YLITG A 2000	2000	1	3	1.15	58 - 180	323	49
YLITG B 2000	2000	1	3	1.15	180 - 300	323	50
YLITG A 3000	3000	1	3	1.5	74 - 180	382	82
YLITG B 3000	3000	1	3	1.4	180 - 300	382	84
YLITG A 5000	5000	2	3	2.0	98 - 180	550	130
YLITG B 5000	5000	2	3	1.8	180 - 300	550	134
YLITG B 10000	10000	3	3	1.8	125 - 310	784	202
YLITG B 20000	20000	6	3	9.5	180 - 310	on request	on request