

Easy Reach Jib (ERJ)



Our best selling Easy Reach Jib offers the ideal solution for dedicated fork trucks lifting loads at a multiple load centre. To fit; simply remove the bottom rear hangers on the attachment back plate. Then simply lower the truck carriage and drive slowly forwards so as the truck carriage top rail contacts the jib backplate just below the attachments top hanger, raise the carriage if necessary so that a snug fit is achieved. Then simply re-fit the bottom hangers and ensure the jib is secured fully. Lifting may now commence.

CONTACT Easy Reach Jibs are standard jib attachments for mounting directly to the fork truck carriage. Beam profile allows access in confined spaces.

Model Ref.	Weight	C of G
500-0.8	75kgs	450mm
500-1.0	80kgs	450mm
500-1.3	83kgs	450mm
500-1.8	83kgs	602mm
500-2.2	88kgs	602mm
500-2.7	95kgs	715mm
500-3.1	98kgs	730mm
500-3.5	120kgs	765mm
500-4.4	130kgs	920mm
600-5.0	145kgs	970mm
600-5.5	150kgs	970mm
600-6.5	254kgs	970mm
600-7.4	254kgs	970mm

Model Ref.	Truck Capacity	"A" Hook Height	"B" Last Hole	Carriage Cl.	Carriage Wid.	Carriage Hei.
500-0.8	1000kgs	38mm	1750mm	2	400mm	500mm
500-1.0	1300kgs	38mm	1750mm	2	400mm	500mm
500-1.3	1500kgs	17mm	1750mm	2	400mm	500mm
500-1.8	2000kgs	- 2mm	1750mm	2	400mm	500mm
500-2.2	2500kgs	1mm	1750mm	2	400mm	500mm
500-2.7	3000kgs	234mm	1750mm	3	500mm	600mm
500-3.1	3500kgs	221mm	1750mm	3	500mm	600mm
500-3.5	4000kgs	195mm	1750mm	3	500mm	600mm
500-4.4	5000kgs	185mm	1750mm	4	500mm	750mm
600-5.0	5500kgs	185mm	1750mm	4	500mm	750mm
600-5.5	6000kgs	44mm	1750mm	4	500mm	750mm
600-6.5	7000kgs	44mm	1750mm	4	500mm	750mm
600-7.4	8000kgs	44mm	1750mm	4	500mm	750mm

Model Ref.	Capacity (kgs) @ Load Centre (mm)					
	500	750	1000	1250	1500	1750
500-0.8	800	650	500	380	310	230
500-1.0	1000	800	630	470	390	280
500-1.3	1300	900	680	500	450	380
500-1.8	1800	1400	1100	900	720	580
500-2.2	2200	1800	1400	1100	1000	850
500-2.7	2700	2050	1450	1200	1100	900
500-3.1	3100	2500	1900	1500	1200	1000
500-3.5	3500	2700	2000	1600	1300	1100
500-4.4	4400	3400	2700	2200	1850	1400
600-5.0	5000	3650	2950	2500	2200	1850
600-5.5	5500	4050	3250	2750	2400	2050
600-6.5	6500	5400	4200	3300	2900	2400
600-7.4	7400	6150	4800	3750	3315	2750

