

Our high quality nylon 6,6 UV stabilised cable ties are available in black only and come packed in 100's. They can be tightened by hand or using one of our tensioning tools. Our UV stabilised cable ties are randomly tested prior to despatch to ensure the highest levels of quality and strength.

This product has the certifications below:



Colours Available:

■ Black

Material Specification:

- Material: Nylon 6,6
- Flammability Rating: UL94-V2
- Installation Temperature: -20oC to +85oC
- Working Temperature: -40oC to +85oC
- Our Standard Cable Ties are RoHS compliant, Low Smoke Generating & Zero Halogen

Strength Specification:

The majority of our UV cable ties are tensile tested randomly before despatch to ensure they are at least meeting, but in the majority of cases well exceeding the minimum tensile strengths quoted below:

- 2.5mm Wide Cable Ties – 8.1kg (18lbs)
- 3.6mm Wide Cable Ties – 18.2kg (40lbs)
- 4.8mm Wide Cable Ties – 22.2kg (50lbs)
- 7.6mm Wide Cable Ties – 54.4kg (120lbs)
- 9.0mm Wide Cable Ties – 79.4kg (175lbs)
- 13mm Wide Cable Ties – 114kg (250lbs)

UV Stabilised Cable Ties

Part Number	Size (Length & Width)	Box Quantity	Pack Quantity	Max Bundle Diameter	Minimum Loop Tensile Strength
C10025BUV	100 x 2.5mm	55,000	100	22mm	8kg
C14036BUV	140 x 3.6mm	30,000	100	33mm	18kg
C20036BUV	200 x 3.6mm	20,000	100	50mm	18kg
C20048BUV	200 x 4.8mm	15,000	100	50mm	22kg
C30048BUV	300 x 4.8mm	11,000	100	80mm	22kg
C37048BUV	370 x 4.8mm	9,000	100	102mm	22kg
C37076BUV	370 x 7.6mm	4,000	100	102mm	54.4kg
C43048BUV	430 x 4.8mm	7,500	100	120mm	22kg
C43090BUV	430 x 9.0mm	2,500	100	116mm	79.4kg
C58013BUV	580 x 13mm	1,200	100	152mm	114kg
C71090BUV	710 x 9.0mm	2000	100	207mm	79.4kg

Data Sheet – UV Stabilised Cable Ties

All Specifications
are Subject to
change