

***DO NOT RUN VEHICLE MOTOR OR USE ANY FUEL-BURNING APPLIANCE THAT CAN CAUSE FUMES TO COLLECT INSIDE TENT OR VEHICLE.**

***TO AVOID BURNS OR DAMAGE TO TENT, CARE SHOULD BE TAKEN NOT TO COME IN CONTACT WITH VEHICLE MUFFLER OR PARTS WHICH MAY BE HOT.**

***DO NOT LEAVE CHILDREN UNSUPERVISED**

Initial installation: The TailVeil adjusts to fit most vehicles with an upward lifting lift-gate. The height adjustment is found on the driver's side just above the bumper skirt junction. The width adjustment is found inside the tent in the center of the bumper skirt. Tension buttons retain your settings.

To install:

Place the unfolded tent on the ground directly behind the vehicle with the skirt edge towards the bumper. Affix the wheel hooks to the wheel or inner edge of wheel well. Grasp the body band and lift it onto the roof of the vehicle forward of the lift-gate hinge, centering the roof panel. To aid single-handed installation, place a magnet (not included) on the body band to hold in place while you move to the other side, or shut one of the roof straps in the rear passenger door or window to hold. Grasp the floor loops hanging near the rear wheels pull straight downward to the ground and stake. Unzip the tent door, reach or stand inside. Open the lift-gate slowly making sure fabric is not caught and it is free to open. From outside the tent pull the floor outward and stake the remaining two corners.

If your vehicle has contours which may cause gaps on the sides, placing a magnet in the area will help prevent insect entry.

SPRA Designs, LLC
4819 Greenleaf Rd.
Sarasota, FL 34233
info@tailveil.com
www.tailveil.com

