

## Safety Data Sheet Ink PK Blend REV

Version 1.1

Revision Date: 09/29/2016

### SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

**Product name** : Ink PK Blend REV

#### Recommended use of the chemical and restrictions on use

Recommended use : Solvent.

#### Manufacturer or supplier's details

**Company** : INX PRODUCTS  
**Address** : 4030 KIDRON RD STE 14  
LAKELAND, FL. 33811  
United States of America

**Emergency telephone number:**  
INX PRODUCTS:-863-646-9830

**Additional Information:** : Phone: 863-646-9830

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS Classification

Flammable liquids : Category 2  
Acute toxicity (Inhalation) : Category 3  
Skin irritation : Category 2  
Eye irritation : Category 2A  
Reproductive toxicity : Category 2  
Specific target organ toxicity - single exposure : Category 3 (Central nervous system)  
Specific target organ toxicity - repeated exposure : Category 2 (Central nervous system, Peripheral nervous system)  
Aspiration hazard : Category 1

#### GHS Label element

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.

## Safety Data Sheet Ink PK Blend REV

Version 1.1

Revision Date: 09/29/2016

H331 Toxic if inhaled.  
H336 May cause drowsiness or dizziness.  
H361 Suspected of damaging fertility or the unborn child.  
H373 May cause damage to organs through prolonged or repeated exposure.

### Precautionary statements

#### : **Prevention:**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

#### **Response:**

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304 + P340 + P311 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P331 Do NOT induce vomiting.  
P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P362 Take off contaminated clothing and wash before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

#### **Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

#### **Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards

## Safety Data Sheet Ink PK Blend REV

Version 1.1

Revision Date: 09/29/2016

The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity: 6.5392 %

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Hazardous components

CAS-No.	Chemical Name	Weight %
68410-97-9 / 64742-49-0 / 64742-89-8	Distillates, pet, lt dist hydrotreat process, low-boil AND/OR Naphtha (pet), hydrotreated lt AND/OR Solvent naphtha (pet), lt aliph.	50 - 70
107-41-5	Hexylene glycol	10 - 20
111-76-2	2-Butoxy ethanol	10 - 20
111-65-9	**Octane	1 - 5
142-82-5	**Heptane	1 - 5

Any Concentration shown as a range is due to batch variation.

**Special Notes:** : \*\* Other substances in the product which may present a health or environmental hazard.

### SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.  
Do not leave the victim unattended.
- If inhaled : Call a physician or poison control centre immediately.  
If unconscious place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

## Safety Data Sheet Ink PK Blend REV

Version 1.1

Revision Date: 09/29/2016

### SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known
- Specific extinguishing methods : Use a water spray to cool fully closed containers.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.  
Use personal protective equipment.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

### SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge

## Safety Data Sheet Ink PK Blend REV

Version 1.1

Revision Date: 09/29/2016

(which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

- Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Prevent unauthorized access.  
No smoking.  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

CAS-No.	Components	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
68410-97-9 / 64742-49-0 / 64742-89-8	Distillates, pet, It dist hydrotreat process, low-boil AND/OR Naphtha (pet), hydrotreated It AND/OR Solvent naphtha (pet), It aliph.	TWA	500 ppm 2,000 mg/m <sup>3</sup>	OSHA Z-1
		TWA	400 ppm 1,600 mg/m <sup>3</sup>	OSHA P0
107-41-5	Hexylene glycol	C	25 ppm	ACGIH
		C	25 ppm 125 mg/m <sup>3</sup>	NIOSH REL
		C	25 ppm 125 mg/m <sup>3</sup>	OSHA P0
111-76-2	2-Butoxy ethanol	TWA	20 ppm	ACGIH
		TWA	5 ppm 24 mg/m <sup>3</sup>	NIOSH REL
		TWA	50 ppm 240 mg/m <sup>3</sup>	OSHA Z-1
		TWA	25 ppm 120 mg/m <sup>3</sup>	OSHA P0

## Safety Data Sheet Ink PK Blend REV

Version 1.1

Revision Date: 09/29/2016

111-65-9	**Octane	TWA	300 ppm	ACGIH
		TWA	75 ppm 350 mg/m <sup>3</sup>	NIOSH REL
		C	385 ppm 1,800 mg/m <sup>3</sup>	NIOSH REL
		TWA	500 ppm 2,350 mg/m <sup>3</sup>	OSHA Z-1
		TWA	300 ppm 1,450 mg/m <sup>3</sup>	OSHA P0
		STEL	375 ppm 1,800 mg/m <sup>3</sup>	OSHA P0
		TWA	300 ppm	ACGIH
142-82-5	**Heptane	TWA	85 ppm 350 mg/m <sup>3</sup>	NIOSH REL
		C	440 ppm 1,800 mg/m <sup>3</sup>	NIOSH REL
		TWA	500 ppm 2,000 mg/m <sup>3</sup>	OSHA Z-1
		TWA	400 ppm 1,600 mg/m <sup>3</sup>	OSHA P0
		STEL	500 ppm 2,000 mg/m <sup>3</sup>	OSHA P0
		TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH

### Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.  
In the case of vapour formation use a respirator with an approved filter.

### Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : Avoid contact with skin, eyes and clothing.  
When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and immediately after handling the product.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

## Safety Data Sheet Ink PK Blend REV

Version 1.1

Revision Date: 09/29/2016

Appearance	: liquid
Colour	: Clear, Colorless
Odour	: characteristic
Odour Threshold	: No data available
pH	: No data available
Freezing Point	: No data available
Boiling Point	: No data available
Flash point	: 10 °C (50 °F) Method: Tag closed cup
Evaporation rate	: 1 Ethyl Ether
Flammability (solid, gas)	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: > 1 (Air = 1.0)
Relative density	: 0.8 @ 25 °C (77 °F) Reference substance: (water = 1)
Density	: 0.8 g/cm <sup>3</sup> @ 25 °C (77 °F)
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Thermal decomposition	: No data available

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reac-	: No hazards to be specially mentioned.

## Safety Data Sheet Ink PK Blend REV

Version 1.1

Revision Date: 09/29/2016

tions

- Conditions to avoid : Keep away from heat, flame, sparks and other ignition sources.  
Do not allow evaporation to dryness.
- Incompatible materials : Strong acids  
Strong oxidizing agents  
strong reducing agents

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

##### Product:

- Acute oral toxicity : Acute toxicity estimate: 4,339 mg/kg
- Acute inhalation toxicity : Acute toxicity estimate: 1029 ppm  
Exposure time: 4 h  
Test atmosphere: gas
- Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg

##### Components:

###### **68410-97-9 / 64742-49-0 / 64742-89-8:**

- Acute oral toxicity : LD50 (Rat, male and female): > 5,000 mg/kg  
Assessment: The substance or mixture has no acute oral toxicity
- Acute inhalation toxicity : Assessment: The component/mixture is toxic after short term inhalation.
- Acute dermal toxicity : LD50 (Rabbit, male and female): > 2,000 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity

###### **111-76-2:**

- Acute oral toxicity : LD50 (Rat): 745 mg/kg  
Assessment: The component/mixture is moderately toxic after single ingestion.

#### Skin corrosion/irritation

##### Components:

###### **68410-97-9 / 64742-49-0 / 64742-89-8:**

- Species: Rabbit  
Exposure time: 4 h  
Result: Irritating to skin.



## Safety Data Sheet Ink PK Blend REV

Version 1.1

Revision Date: 09/29/2016

### Serious eye damage/eye irritation

#### Components:

**68410-97-9 / 64742-49-0 / 64742-89-8:**

Species: Rabbit

Result: Irritating to eyes.

**107-41-5:**

Species: Rabbit

Result: Irritating to eyes.

**111-76-2:**

Species: Rabbit

Result: Irritating to eyes.

### Respiratory or skin sensitisation

#### Components:

**68410-97-9 / 64742-49-0 / 64742-89-8:**

Test Type: Buehler Test

Species: Guinea pig

Result: Did not cause sensitisation on laboratory animals.

### Germ cell mutagenicity

#### Components:

**68410-97-9 / 64742-49-0 / 64742-89-8:**

Germ cell mutagenicity - Assessment : Mutagenicity classification not possible from current data

### Carcinogenicity

#### Components:

**68410-97-9 / 64742-49-0 / 64742-89-8:**

Carcinogenicity - Assessment : Carcinogenicity classification not possible from current data.

<b>IARC</b>	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
<b>OSHA</b>	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
<b>NTP</b>	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
<b>ACGIH</b>	Confirmed animal carcinogen with unknown relevance to humans
	111-76-2 2-Butoxy ethanol

## Safety Data Sheet Ink PK Blend REV

Version 1.1

Revision Date: 09/29/2016

### Reproductive toxicity

#### Components:

**68410-97-9 / 64742-49-0 / 64742-89-8:**

Reproductive toxicity - Assessment : Fertility classification not possible from current data.

Teratogenicity - Assessment : Embryotoxicity classification not possible from current data.

### STOT - single exposure

#### Components:

**68410-97-9 / 64742-49-0 / 64742-89-8:**

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness., The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

### STOT - repeated exposure

#### Components:

**68410-97-9 / 64742-49-0 / 64742-89-8:**

Target Organs: Central nervous system, Peripheral nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

### Aspiration toxicity

#### Components:

**68410-97-9 / 64742-49-0 / 64742-89-8:**

May be fatal if swallowed and enters airways.

### Further information

#### Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause narcotic effects.

Solvents may degrease the skin.

#### Components:

**68410-97-9 / 64742-49-0 / 64742-89-8:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause narcotic effects.

Solvents may degrease the skin.

## Safety Data Sheet Ink PK Blend REV

Version 1.1

Revision Date: 09/29/2016

### SECTION 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

##### Components:

##### **68410-97-9 / 64742-49-0 / 64742-89-8:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 8.2 mg/l  
Exposure time: 96 h  
Test Type: semi-static test

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 4.5 mg/l  
aquatic invertebrates Exposure time: 48 h  
Test Type: Immobilization

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 3.7  
Exposure time: 96 h  
Test Type: static test

Acute aquatic toxicity- As- : Toxic to aquatic life.  
essment

Chronic aquatic toxicity- As- : Toxic to aquatic life with long lasting effects.  
essment

#### Persistence and degradability

##### Product:

Biodegradability : Remarks: No data available

##### Components:

##### **68410-97-9 / 64742-49-0 / 64742-89-8:**

Biodegradability : Result: Readily biodegradable  
Biodegradation: 77 %  
Testing period: 2 d  
Exposure time: 28 d

#### Bioaccumulative potential

##### Components:

##### **111-65-9:**

Partition coefficient: n- : log Pow: 5.15  
octanol/water

#### Mobility in soil

No data available

#### Other adverse effects

##### Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Pro-

## Safety Data Sheet Ink PK Blend REV

Version 1.1

Revision Date: 09/29/2016

tection of Stratospheric Ozone - CAA Section 602 Class I Substances  
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Toxic to aquatic life with long lasting effects.

### Components:

#### **68410-97-9 / 64742-49-0 / 64742-89-8:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Toxic to aquatic life with long lasting effects.

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### **Disposal methods**

Waste from residues : Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

## SECTION 14. TRANSPORT INFORMATION

### **DOT (Department of Transportation):**

UN1263, PAINT RELATED MATERIAL, 3, II

### **IATA (International Air Transport Association):**

UN1263, PAINT RELATED MATERIAL, 3, II

### **IMDG (International Maritime Dangerous Goods):**

UN1263, PAINT RELATED MATERIAL, 3, II, Marine Pollutant (DISTILLATES (PETROLEUM), LIGHT DISTILLATE HYDROTREATING PROCESS, LOW-BOILING, OCTANE) , Flash Point:10 °C(50 °F)

---

## SECTION 15. REGULATORY INFORMATION

**WHMIS Classification** : B2: Flammable liquid  
D1A: Very Toxic Material Causing Immediate and Serious Toxic Effects  
D2B: Toxic Material Causing Other Toxic Effects

**EPCRA - Emergency Planning and Community Right-to-Know Act**



# Safety Data Sheet

## Ink PK Blend REV

Version 1.1

Revision Date: 09/29/2016

### CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
**Benzene	71-43-2	10	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Fire Hazard  
Immediate (Acute) Health Hazard  
Chronic (Delayed) Health Hazard

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

111-76-2            2-Butoxy ethanol

### Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCOMI Intermediate or Final VOC's (40 CFR 60.489):

111-76-2            2-Butoxy ethanol

### Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

108-88-3            \*\*Toluene  
100-41-4            \*\*Ethylbenzene  
71-43-2             \*\*Benzene  
91-20-3             \*\*Naphthalene

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

108-88-3            \*\*Toluene  
100-41-4            \*\*Ethylbenzene  
71-43-2             \*\*Benzene  
91-20-3             \*\*Naphthalene

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

### US State Regulations

#### Massachusetts Right To Know

107-41-5	Hexylene glycol	10 - 20 %
111-76-2	2-Butoxy ethanol	10 - 20 %
111-65-9	**Octane	1 - 5 %
142-82-5	**Heptane	1 - 5 %
71-43-2	**Benzene	0 - 0.1 %

#### Pennsylvania Right To Know

**Safety Data Sheet**  
**Ink PK Blend REV**

Version 1.1

Revision Date: 09/29/2016

68410-97-9 / 64742-49-0 / 64742-89-8	Distillates, pet, lt dist hydrotreat process, low-boil AND/OR Naphtha (pet), hy- drotreated lt AND/OR Solvent naphtha (pet), lt aliph.	50 - 70 %
107-41-5	Hexylene glycol	10 - 20 %
111-76-2	2-Butoxy ethanol	10 - 20 %
111-65-9	**Octane	1 - 5 %
142-82-5	**Heptane	1 - 5 %
107-21-1	Ethylene glycol	0.1 - 1 %
108-88-3	**Toluene	0 - 0.1 %
100-41-4	**Ethylbenzene	0 - 0.1 %

**New Jersey Right To Know**

68410-97-9 / 64742-49-0 / 64742-89-8	Distillates, pet, lt dist hydrotreat process, low-boil AND/OR Naphtha (pet), hy- drotreated lt AND/OR Solvent naphtha (pet), lt aliph.	50 - 70 %
107-41-5	Hexylene glycol	10 - 20 %
111-76-2	2-Butoxy ethanol	10 - 20 %
111-65-9	**Octane	1 - 5 %
142-82-5	**Heptane	1 - 5 %

**California Prop 65**

100-41-4	WARNING! This product contains a chemical known to the State of California to cause cancer. **Ethylbenzene	
71-43-2	**Benzene	
91-20-3	**Naphthalene	
	WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.	
107-21-1	Ethylene glycol	
108-88-3	**Toluene	
71-43-2	**Benzene	

**The components of this product are reported in the following inventories:**

TSCA	: On TSCA Inventory
DSL	: All components of this product are on the Canadian DSL
AICS	: On the inventory, or in compliance with the inventory
NZIoC	: On the inventory, or in compliance with the inventory
ENCS	: Not in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory

# Safety Data Sheet


## Ink PK Blend REV

Version 1.1

Revision Date: 09/29/2016

### SECTION 16. OTHER INFORMATION

**NFPA:**



**HMIS III:**

<b>HEALTH</b>	<b>2*</b>
<b>FLAMMABILITY</b>	<b>3</b>
<b>PHYSICAL HAZARD</b>	<b>0</b>

0 = not significant, 1 = Slight,  
 2 = Moderate, 3 = High  
 4 = Extreme, \* = Chronic

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**Revision Date** : 09/29/2016

**Legacy SDS:** : R0311201

**Material number:**  
 16113257, 542617, 131726

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic

## Safety Data Sheet Ink PK Blend REV

Version 1.1

Revision Date: 09/29/2016

GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50			Lethal Concentration 50%