

DP7 Professional Drum and Percussion Mic Package

LIVE SOUND OR RECORDING

Whether on stage or in the studio, the DP7 drum pack is the ideal collection of seven microphones for the standard five piece drum kit. Audix VLM™ dynamic mics manage the transients of the drums at close range while the condensers capture the cymbals and a stereo image of the entire kit from overhead. This award-winning combination of microphones, clips and mounting accessories is packaged securely within a rugged aluminum carrying case.

- Professional set of 7 drum mics for stage or studio
- ADX51 condensers for overheads add spacial dimension
- Recognized industry-wide for exceptional performance and consistency

CLOSE MIKING

The D6 for kick drum and the i5 for snare are must-haves for every drummer. The kick and snare are considered the core of any drum kit and the foundation for every groove. Close miking insures that they will be captured in the mix. If either the kick or the snare is unable to be heard, there is simply no groove. The D2 and D4 are industry standards for toms and floor toms. Being high SPL dynamic microphones, the D6, i5, D2 and D4 excel at “close miking”. This miking technique is required in order to capture the attack and percussive sound of the drum. By having the mic close to the source of the sound, it helps to isolate and control the sound of each drum.

OVERHEAD MIKING (ambient)

Supporting the idea that “less is more”, many engineers will use just two overhead mics to capture the natural sound of the complete drum kit. With two overhead mics, positioned correctly, it is absolutely true that you can capture the transients, tonality and balance of the kit in a completely phase-coherent manner.

The ADX51, a pre-polarized condenser microphone with a 14mm gold sputtered diaphragm, is designed with overhead applications in mind. Due to its cardioid pickup pattern, high sensitivity and slim pencil design, the two ADX51 mics can be easily positioned overhead to provide a nice stereo image of the entire drum kit.

THE BLEND

With contemporary music and the volumes typically generated on stage, it is more practical and effective to create a blended effect of close miking and a stereo image of the entire kit from overhead. The D6 will help provide the earthshaking lows and the attack of the kick; the i5 will reinforce the depth and crack of the snare; the D2 and D4 will pick up the attack and overtones of the toms, and the ADX51 overheads will pick up the hi-hat, cymbals and the ambience of the entire kit. With the DP7, drums will maintain their sound integrity and critical presence, regardless of the size of the room and PA system.



INCLUDES

- PACKAGED SET OF 7 DRUM MICS
- Aluminum Road Case
- 1 x i5 Snare Mic
- 2 x D2 Rack Tom Mics
- 1 x D4 Floor Tom Mic
- 1 x D6 Kick Drum Mic
- 2 x ADX51 Overhead Mics
- 4 x DVICE Rim Mounts
- 3 x DCLIP Mic Clips
- 1 x MC1 Mic Clip
- 2 x WS81C Windscreens

SUPPLIED ACCESSORIES

- DVICE** - Spring loaded rim mount clamp
- MC1** - Nylon mic clip
- DCLIP** - Heavy duty mic clip provided with D Series
- WS81C** - Foam windscreen for reducing wind, sibilance and pop noise

OPTIONAL ACCESSORIES

- DFLEX** - All purpose percussion clamp
- DCLAMP** - Tension rod mic clamp
- STANDKD** - Adjustable kick drum mic stand with telescopic boom
- CBL20** - 20' XLR-XLR mic cable
- CBLDR25** - 25' right angle XLR-XLR mic cable



DVICE



MC1



DCLIP



WS81C



DFLEX



DCLAMP



STANDKD



CBL20



CBLDR25

DP7

SPECIFICATIONS



Transducer	Dynamic VLM Type B	Dynamic VLM Type B	Dynamic VLM Type D	Dynamic VLM Type B	Pre-Polarized Con- denser
Frequency Response	50 Hz - 16 kHz	68 Hz - 18 kHz	40 Hz - 18 kHz	30 Hz - 15 kHz	40 Hz - 18 kHz
Polar Pattern	Cardioid	Hypercardioid	Hypercardioid	Cardioid	Cardioid
Output Impedance	150 ohms	280 ohms	280 ohms	280 ohms	100 ohms
Sensitivity	1.5 mV / Pa @ 1k	1.2 mV / Pa @ 1k	1.4 mV / Pa @ 1k	0.8 mV / Pa @ 1k	17 mV / Pa @ 1k
Maximum SPL	≥140 dB	≥144 dB	≥144 dB	≥144 dB	≥132 dB
Off-axis rejection	≥23 dB	≥30 dB	>20 dB	>20 dB	>15 dB
Power Requirements	None	None	None	None	9-52 V phantom
Materials / Finish	Zinc Alloy/ Black Finish	Black Hard Coat	Black Hard Coat	Black Hard Coat	Brass / Black Finish
Weight	250 g / 8.8 oz	250 g / 8.8 oz	128 g / 4.5 oz	254 g / 8.9 oz	184 g / 6.5 oz
Length	141.5 mm / 5.6 in	100 mm / 3.9 in	100 mm / 3.9 in	117 mm / 4.6 in	160 mm / 6.3 in

USER TIPS

This package is identical to the DP5A with the addition of two ADX51 condensers for overhead miking. With the addition of the overhead mics, you now have the opportunity to create more depth of field and more presence within the mix. You have the choice of using both ADX51s for overheads or one for hi-hat and one for overhead.

ADX51 - As overheads: The most common positioning concept is to keep the snare as the focal point and move the mics into various left and right positions equal distance from the snare; 4 feet is a good starting point. For best results, keep the mics in a vertical position, keeping in mind that you are not necessarily just miking the cymbals but the whole kit. You will find after some experimentation that the kick, snare, and overheads will provide most of your sound while the tom mics are used for sweetening.

ADX51 - One for hi-hat, one for overhead: The ADX51 for high hat should be placed 2-3 inches above the top cymbal and towards the outside edge. The overhead mic can be placed overhead above the cymbals, generally above the rack toms. In the case where there are more cymbals on one side of the kit than the other, the mic can favor the side with the most cymbals.

i5 - Snare: A good starting point is 2 inches above the rim with the mic pointing towards the center of the head. For more "rim" sound, pull the mic closer to the rim. For more resonance and depth of field, pull the mic farther away from the head. The trick is to find the right balance between resonance and attack while still controlling bleed from the other drums.

D2 / D4 - Floor Toms: Place the mic about 2 inches above the head and point the mic across the head towards the center of the drum. This is the best position to capture the fundamental resonance and decay of the drum with minimal ring.

Note that you will need the DCLAMP or DFLEX mounts in order to attach the mics to hand percussion instruments or non-conventional rims.

D6 - Kick Drum: To position the D6, a good starting point is a few inches inside the port of the front head with the mic pointing off-center and not directly at the beater. For more attack, move the mic closer towards the beater. For more bass, pull the mic farther away from the beater.

For more information please visit www.audixusa.com to view our six part video on "How to Mic Your Kit."

PRODUCT REGISTRATION: Please register your product online at www.audixusa.com/docs_12/about/product_registration.shtml.

SERVICE AND WARRANTY: The i5, D2, D4, and D6 microphones are under warranty for a period of 5 years and the ADX51 microphone is under warranty for a period of 3 years to be free of defects in material and workmanship. In the event of a product failure due to materials or workmanship, Audix will repair or replace said product at no charge with proof of purchase. Audix does not pay or reimburse shipping costs for warranty repairs or returns. The warranty excludes any causes other than manufacturing defects, such as normal wear, abuse, environmental damage, shipping damage or failure to use or maintain the product per the supplied instructions. No Implied Warranties: All implied warranties, including but not limited to implied warranties of merchantability and fitness for a particular purpose are hereby excluded. The liability of Audix, if any, for damages relating to allegedly defective products shall be limited to the actual price paid by Dealer for such products and shall in no event include incidental or consequential damages of any kind. Should your microphone fail in any way, please contact the Audix Service department at 503.682.6933. A Return Authorization is required before returning any product. OTHER THAN THIS WARRANTY, AUDIX MAKES NO WARRANTIES, EXPRESS OR IMPLIED, WITH RESPECT TO THE PRODUCTS, THE USE OF THE PRODUCTS, THE PERFORMANCE OF THE PRODUCTS. AUDIX SHALL NOT BE LIABLE FOR SPECIAL INCIDENTAL, CONSEQUENTIAL, INDIRECT OR SIMILAR DAMAGES ARISING FROM OR BASED ON THE SALE, USE, STORAGE OR DISPOSAL OF THE PRODUCTS, AUDIX'S SERVICE WORK, BREACH OF WARRANTY, BREACH OF CONTRACT. NEGLIGENCE, OR ANY OTHER THEORY OF LIABILITY, EVEN IF AUDIX HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.



www.audixusa.com
503.682.6933 Fax: 503.682.7114
Audix Corporation 9400 SW Barber St. Wilsonville, OR 97070

AUDIX

ver 4.0 12.17