

# TYPHON™

## IP WASH



## IP66-rated Moving Wash

### Outdoor Wash w/Zoom

Typhon™ IP Wash is a professional IP66-rated LED moving wash fixture, designed to deliver ultra-bright, vibrant colors in outdoor environments. Equipped with 19x 40W OSRAM® 4-in-1 RGBW LEDs, it offers a broad spectrum of colors and effects. The fixture features a motorized zoom from a focused 6° beam to a wide 55° field angle. Its speed-controllable pan (360/540°) and tilt (230°) movements are precise and fluid. Enhanced with both 8-bit and fine 16-bit resolution, the Typhon™ IP Wash ensures smooth dimming, color mixing, and control of individual effects.

### Loaded with Features

This fixture offers both full color and 3-zone LED ring effects, and it comes loaded with 16 color/pattern presets, 10 chase macros, and 21 built-in CCT color presets that range from a 3200K warm white to a cool 7200K. Other features include 1-25Hz strobe with synchronized and pulse effects, and 4 user-selectable dimming curves for customized lighting control. Additionally, the fixture has integrated dual mounting clamps for easy rigging, and for reliable power and data connectivity, it has powerCON® TRUE1-compatible power input and 5-pin DMX in/out connections.

### Main Features

- Professional IP66-rated LED moving wash fixture
- 19x 40W OSRAM® 4-in-1 RGBW LEDs, 50,000 hrs.
- Pan: 360/540°, Tilt: 230° (8-16 bit resolution)
- Adjustable pan/tilt speed
- Motorized zoom (6°-33° beam, 9°-55° field angle)
- 0% - 100% electronic dimming
- Full color and 3-zone LED ring effects
- 16 static color presets, 10 built-in color chase macros
- 1-25Hz strobe, synchronized + pulse effects
- CCT colors from 3200K-7200K, CRI: ≥70
- 4x user selectable dimming curves
- Internal fan cooling system
- Secure pan/tilt locks for safe transport
- Integrated dual clamp mounting assembly



#### Optical

19x 40W OSRAM® RGBW LEDs  
 6°-33° beam angle, 9°-55° field angle  
 Luminous Intensity  
 12,500 Lux @ 7.5M (6°)  
 563 Lux @ 7.5M (33°)  
 7,070 Lux @ 10M (6°)  
 320 Lux @ 10M (33°)



#### Weight & Dimensions

18.6" x 11" x 20.9" (472.7 x 280 x 529.5 mm)  
 50.7 lbs. (23 kg)



#### Control

Protocol: USITT DMX-512, RDM  
 5-pin DMX in/out  
 23/15/39-channel DMX  
 5-button menu with LCD display  
 DMX512, M/S, auto mode



#### Power + Current

100-240VAC, 50-60 Hz  
 Consumption: 965W, 10A, PF: .96  
 Fuse: 15A/250V  
 PowerCON® TRUE1-compatible input



#### Warranty + Certifications

2-year limited warranty