

Amhaze ECO



SPECIFICATIONS

Dynamic Effects

- Fan Speed: 120 cfm
- Low Fluid Shutdown: Yes

Optional Accessories

- Clamps
- Neutrik® powerCON® cables
- DMX Cables

FEATURES

- Professional water-based haze machine
- 30-sec heat up time nearly eliminates wait time for operation
- Continuous output with no reheating required
- Tour-ready with an M12 threaded insert for truss clamps
- Efficient fluid consumption lasts more than 8 hours on a single fluid container
- Achieve continuous variable haze output and blower speed, adjusted via DMX or manual knobs

Construction / Physical

- Dimensions: 15.86 in (403 mm) x 12.20 in (310 mm) x 10.07 (256 mm)
- Dimensions (shipping size): 20.27 x 16.53 x 12.80 in (515 x 420 x 325 mm)
- Weight: 25 lb (11.4 kg)
- Weight: (shipping weight): 28.8 lb (13.5 kg)
- Threaded Bolt: M12
- Exterior Color: Black
- Tank Capacity: 0.92 gal (3.5L)
- Fluid Consumption: 7 ml/min (0.11 gallons/hour)
- Maximum Run time: >8 hours @ full volume
- Rest on the floor or mount in the rig with the M12 threaded insert for truss clamps

Connections

- Power Connection: Edison (local) plug to Seetronic Powerkon IP65
- Power Input: Seetronic Powerkon IP65
- Data Connectors: 3- and 5-pin XLR
- Cable Length (power): 5 ft (1.5 m)

Control

- Control Protocol: DMX, RDM DMX Channels: 3

- DMX Channels: 3
- Modes/Personalities: 1 personality
- On-Board Control: Yes

Electrical

- Input Voltage: 120 VAC, 60 Hz or 230 VAC, 50 Hz
- Power and Current: 1,230 W, 10.25 A @ 120 V, 60 Hz
- Power and Current: 2,430 W, 10.56 A @ 230 V, 50 Hz
- Heat-up Time: 30 sec

Certifications / Qualifications

- MET, CE
- MET Listing Number: E115095
- US Safety: UL 499
- Canadian Safety: CSA C22.2 No. 64-10
- IP Rating: IP20, dry location
- Minimum distance from flammable material to all exterior surfaces of the product: 3.3 ft (1 m)
- Maximum exterior surface temperature (Tc): 127 °F (53 °C)

What's Included

- Amhaze Eco
- Seetronic Powerkon IP65 power cord