



Cosmo C1

1000ft Wireless SDI&HDMI Transmission System, transformed by Hollyland's HEVO wireless transmission technology, offers a new standard for real-time video monitoring and a simplified solution to stream and cloud-share your video works.



1000ft



Direct UVC Livestream



HEVO Solution



Seamless Frequency Switching



40ms Latency



HDMI + SDI + SDI LOOPOUT

www.hollyland-tech.com



- Ultra-low Latency, As Low As 40ms
- 1,000ft Wireless Transmission Range (LOS)
- Embedded UVC for Direct Live Streaming (P format Only)
- Three Power Supply Options: DC Adaptor, L-series Battery, and USB C
- Auto Channel Switching
- Low-Battery Indicator
- HDMI&SDI In/Out + SDI Loopout
- Seamless Channel Switching

Item	Parameter
Power Supply	DC Power Input 6~16V; USB Type-C Power Supply 5V/2A; Battery Power Supply 6-16V
Power Consumption	<9W
Dimension (mm)	115L*70W*32H (The Battery Plate Exclude)
Frequency	5.1GHz~5.8GHz
Transmission Latency	≈40ms
Bandwidth	20MHz
Weight	214g (Without Exterior Antenna); 210g (Without Exterior Antenna)
TX Input Video Format	HDMI:480p60; 576p50; 720p50/59.94/60; 1080i50/59.94/60; 1080p23.98/24/25/29.9/30 1080p50/59.94/60 SDI:1080p60/59.94/50(Level A); 1080p60/59.94/50(Level B); 1080i60/59.94/50; 1080p30/29.97/25/24/23.98; 720p60/59.94/50; 1080psf30/29.97/25/24/23.98
RX Output Video Format	HDMI:480p60; 576p50; 720p50/60; 1080i50/60; 1080p24/25/30; 1080p50/60 SDI:1080p60/50(Level A); 1080i60/50; 1080p30/29/25/24; 720p60/50