

KDS-7

High-performance,
highly scalable
AVoIP streaming solution



High-performance, highly scalable AVoIP streaming solution

Get a full AVoIP streaming solution for anywhere low-latency, high-quality 4K60 4.2.0 video presentation is required. The KDS-7 line comprises a full range of encoders and decoders, supports 1K video sources, enables simple and fast deployment, and easily scales to suit any size network AV installation. Delivering a superb user experience, enterprise IT-grade security and advanced yet intuitive management, KDS-7 is a perfect fit for enterprise, education, homeland security, military or government sites of any size.

Outstanding end-user experience

- **Rich set of inputs and interfaces**
Featuring multiple connectivity options, including USB-C and HDMI, KDS-7 devices support the vast majority of end-user devices. With USB-C connectivity, end-user devices are charged while they are connected, eliminating the need for an additional power cable.
- **Easy-to-use KVM**
Simplified control via keyboard and/or mouse, with a specially designed widget and navigation among up to 16 screens, with configurable layout.
- **Large-scale video wall controls**
Supports more than 64 screens in different layouts that are easily configurable via the dedicated management device, and switchable in one click using the management device or Kramer Control software.
- **Instantaneous switching**
Optimized for a fast switching time. Switching between streams takes just 1 second or less.

Ideal for large-scale deployments

- **Highly scalable**
The KDS-7 line supports 1K video sources, suited to the largest installations.
- **State-of-the-art management device**
Advanced management capabilities are provided via the dedicated management device, including multi-device grouping, preset virtual matrix stream routes, group configuration management and role-based access management.
- **Extensive set of management capabilities features**
With open P3K APIs, a front panel LCD screen and an intuitive, embedded web-based user interface, KDS-7 devices provide a rich set of tools for deployment and configuration. This enables AV experiences in any space, large or small, and allows management from anywhere for reliable and flexible operational management.

Robust security

- **Enterprise IT-grade security**

KDS-7 devices comply with IT security requirements, including 802.1x and HTTP-S/TLS.

- **Security certification**

All devices carry OWASP Top 10 certification for web application security.

- **Separate ethernet ports for optimal security and experience**

Physical separation between control and AV data over two separate Ethernet ports ensures IT control and an uninterrupted AV experience.

Simple planning and rollout

- **Cost-effective from day one**

Plug-and-play integration with leading IP network switches, such as Netgear M4250 series, enable deployment in a wide variety of network topologies. There is no need to deal with complex IP packets prioritization or switching setting. Offering easy management, high reliability and adjustable bandwidth control, KDS-7 is extremely cost-effective to maintain over the long term

- **Full product range for any site, any application**

The comprehensive KDS-7 line spans encoders, decoders and auto-switcher encoders in a choice of rack and wall-plate* form factors, as well as a dedicated manager device. The broad set of products within the KDS-7 product line allows quick and cost-effective rollout of AV-enabled spaces of all forms and size. The eight different KDS-7 devices can be combined in any way, with any quantity of decoders, according to the site needs.

* Coming soon

- **Fully integrated with Kramer's complete Pro AV solutions**

The KDS-7 line is part of Kramer's market-leading full AVoIP-based solution. It is pre-integrated with Kramer Control, allowing efficient deployment and control of any space, at a fraction of the time and cost of standalone alternatives. It is also integrated with KDS-USB2 for AVoIP remote access to any USB peripheral devices, such as webcams.

Standalone Encoder



For more information:

Interface Type	Inputs/Outputs	Function
LCD and Navigation Button	1	Device configuration
USB 2.0	1	Connection to host
HDMI IN 2.0b	1	Uncompressed input signal
HDMI OUT 2.0b	1	Loop through output
1GbE Ethernet RJ-45	1	Configuration port
1GbE PoE Ethernet RJ-45	1	Content streaming port
External Power Supply	1	Optional, 24V/1A power supply, sold separately
Reset Button	1	Factory reset (10 sec) – Reaction is all LEDs blink
3-Pin Terminal Block IR	1	Programmable bidirectional IR transmission; expected voltage for IR receiver – 3.3 V
5-Pin Terminal Block Audio	1	Programmable analog balanced input/output audio
3-Pin Terminal Block RS-232	1	RS232 gateway and path-through



Approximate dimensions: 190.5 mm x 27.4 mm x 142.0mm (W x H x D)

Auto-Switcher Encoder with Dante® / AES67 Audio Embedding and Deembedding

For more information:



Interface Type	Inputs/Outputs	Function
LCD and Navigation Button	1	Device configuration
HDMI IN 2.0b	1	Uncompressed input signal
USB-C	1	Video, data and power provider
HDMI OUT 2.0b	1	Loop through output
1GbE Ethernet RJ-45	1	Configuration port (service)
1GbE PoE Ethernet RJ-45	1	Content streaming sort (media)
External Power Supply	1	Optional, 24V/5A power supply, sold separately
Reset Button	1	Factory reset (10 sec) – Reaction is all LEDs blink
3-Pin Terminal Block IR	1	Programmable bidirectional IR transmission; expected voltage for IR receiver – 3.3 V
Terminal Block Audio	1	Programmable analogue balanced input/output audio
RS-232	1	RS232 gateway and path-through
USB Host	1	Connection to host
USB Device	2	Connection to device/power provider

Approximate dimensions: 190.5 mm x 27.4 mm x 142.4 mm (W x H x D)

Additional information:

- Programmable Stereo Pair Dante stream In/Out (total 4 channels)
- Supports USB hub functionality
- When USB-C is active as a video source, USB-C is also the USB Host device, otherwise USB-B host in the back is active
- The Dante/AES67-received audio stream can be combined with the video and output via the HDMI output or analog audio output



Standalone Decoder



For more information:

Interface Type	Inputs/Outputs	Function
LCD and Navigation Button	1	Device configuration
HDMI IN 2.0b	1	HDMI2.0 input signal
HDMI OUT 2.0b	1	HDMI2.0 output signal
1GbE Ethernet RJ-45	1	Configuration Port
1GbE PoE Ethernet RJ-45	1	Content streaming port
External Power Supply	1	Optional, 24V/1A power supply, sold separately
Reset Button	1	Factory reset (10 sec) – Reaction is all LEDs blink
3-Pin Terminal Block IR	1	Programmable bidirectional IR transmission; expected voltage for IR receiver – 3.3 V
Terminal Block Audio	1	Programmable analog balanced audio input/output
RS-232	1	RS232 gateway and path-through
USB Device	2	Connection to device/power provider



Approximate dimensions: 190.5 mm x 27.4 mm x 142.6mm (W x H x D)

Manager



For more information:


Interface Type	Inputs/Outputs	Function
LCD and Navigation Button	1	Device configuration
USB 2.0	2	Connection to Kramer Control/power provider
HDMI OUT 1.3	1	Local UI on HDMI Out. 1080P (HDMI 1.3)
1GbE PoE Ethernet RJ-45	1	Configuration port
External Power Supply	1	Optional, 24V/1A power supply, sold separately
Reset Button	1	Factory reset (10 sec) – Reaction is all LEDs blink




Approximate dimensions: 190.5 mm x 27.4 mm x 142.60mm (W x H x D)

* To allow for an easier, cleaner installation, with less rack space, the KDS-7 AVoIP streaming solution includes a rack cage frame for vertical storage of the standalone devices.

Illustration of typical AVoIP system



deployment with KDS-7 product line



About Kramer

Kramer has been at the forefront of the Pro AV IT industry for 40 years. Our global mission focuses on supporting and collaborating with a wide range of enterprise, government, education clients, and more. Wherever Pro AV is essential, Kramer solutions can be found.



www.kramerav.com

© 2022 KRAMER ELECTRONICS, Ltd. All rights reserved.
Reproduction in whole or in part without written permission is prohibited.

Kramer_KDS-7_Feb2022