

EN12-45

TECHNICAL DATA | REV A

OBSIDIAN™
CONTROL SYSTEMS



KEY FEATURES

- RDM, Artnet and sACN support
- Factory and user presets for plug and play setups
- Line Voltage or POE powered
- 1.8" OLED Display with rotary knob
- 99 Internal cues with fade and delay time
- Customizable routing and merging options
- Remote configuration via internal webpage
- Contact closures for cue or preset recall
- Powder-coated aluminum rackmount housing

SPECIFICATIONS

MOUNTING

Rackmount

CONNECTIONS

- Front
 - (12) RJ45 DMX/RDM optically isolated ports (ESTA Compliant)
 - Ports are bidirectional for DMX In and Output
 - Full color OLED display
 - Encoder w. Push to Select / Exit Button

- Back
 - (2) Locking RJ45 Ethernet network In
 - (10) Contact Closures (Terminal Block)
 - Locking Power In/Thru

PHYSICAL

- Length: 482.5 mm (19 in.)
- Width: 146 (5.7mm)
- Height: 44 mm (1.7 in.)
- Weight: 1.82 kg (4 lbs)

ELECTRICAL

- 100-240 V nominal, 50/60 Hz
- POE 802.3af

EN12-45

ORDERING

INCLUDED ITEMS

1.5m Locking power cable (EU or US version)

SKU

US #: NRE302

EU #: 1330000068

FS2LN3

