



KEY FEATURES

- RDM, Art-Net and sACN support
- Factory and user presets for plug and play setups
- POE or USB-C powered
- 1.5" OLED Display with rotary knob
- Remote configuration via internal webpage
- Powder-coated compact aluminum housing
- Connect to ONYX PC for a full four Universe Solution
- In-Wall, On-Wall, Truss and Standalone Mounting

SPECIFICATIONS

MOUNTING

- Standalone
- Truss-mount (M10 or M12 mounting hole)
- In or On-wall 2-Gang (US) or 50mm round EU)

CONNECTIONS

- Front
 - (2) 5pin DMX/RDM optically isolated ports
 - Ports are bidirectional for DMX In and Output
- Side
 - (2) Locking RJ45 Ethernet network connections (1x POE)
 - USB-C power option

PHYSICAL

- INCLUDED ITEMS
- Length: 4.6 in. (117.6mm)
- Width: 4.5 in. (114mm)
- Height: 3.5 in. (89mm)
- Weight: 1.76lbs. (0.8kg)

ELECTRICAL

- USB-C 5V
- POE 802.3af

APPROVALS/RATINGS

- CE / UKCA / IP20



ORDERING

INCLUDED ITEMS

Universal 5V/2A USB Power Adapter (UK, US, Europe, & Aus connectors), 100-240V

1.5m Locking power cable (EU or US version)

Wallmount Enclosure

In-wall mounting rig

SKU

US #: NRE023

EU #: 1330000064

