

RDM6XL

TECHNICAL DATA REV A

OBSIDIAN™
CONTROL SYSTEMS



KEY FEATURES

- (6) XLR 5pin outputs
- DMX and RDM compliant
- Optically isolated ports
- Power / DMX Through connectors
- Powder-coated aluminum 1/2 rack housing

SPECIFICATIONS

MOUNTING

- Standalone
- Truss-mount (M10 or M12 mounting hole)
- Wall-mount horizontal or vertical (included)
- DIN Rail horizontal or vertical (included)
- Rack-mount option (requires NET Shelf)

CONNECTIONS

- Front
 - 5pin DMX Input
 - (6) 5pin Opto-Isolated DMX Outputs
 - RDM Enable

- Back
 - 5pin DMX Input (parallel with front)
 - 5pin DMX Through
 - Terminate
 - Locking Power In/Thru

PHYSICAL

- Length: 215 mm (8.5 in.)
- Width: 139 mm (5.5 in.)
- Height: 42 mm (1.65 in.)
- Weight: 1 kg (2.2 lbs)

ELECTRICAL

- 100-240 V nominal, 50/60 Hz, 10W

APPROVALS/RATINGS

cETLus / CE / IP20



Intertek
5017012

RDM6XL

ORDERING

INCLUDED ITEMS

- 1.5m Locking power cable (EU or US version)
- (2) Wallmount plates
- (2) DIN-Rail clamps

SKU

- US #: NRD123
- EU #: 1330000061

ROMEXL

