# VL600 ACCLAIM PLE WW

Date:
Type:
Firm Name:
Project:

The VL600 Acclaim PLE WW is a 500W / 650W-equivalent fixed white 3200k profile light engine perfect for Front of House positions where color is not needed in small to medium theatres, houses of worship, and education environments. With exceptional output in a fixed warm white luminaire, it is designed for applications where a longer throw or wider spread is needed. Because the VL600 PLE WW works with Vari-Lite's wide range of fixed and zoom lens tubes, ensuring there is a lens for any application. With the onboard fourblade manual shutter system, the VL600 PLE WW offers superior control to shape the light how you want it. Thanks to the optional size B metal gobo holder, designers can project depth and texture on stage, using the angle adjustment and manual focus to get the look just right. For applications where a low trim height is a challenge, the adjustable yoke allows the fixture to be positioned closer to the suspension point to give more headroom. The VL600 Acclaim PLE WW is available in black or white.



\*shown with optional lens tube

- 500W/650W-equivalent profile engine cost-effective ellipsoidal profile
- Fixed 3200K white high output warm white
- Wide range of fixed and zoom lens tubes beam angles for any application
- Four-blade manual shutter system superior control to position light exactly where you need it.
- Optional angle-adjusting size B metal gobo holder add depth and texture using industry-standard gobos. Easily adjust gobo angle within holder to get the perfect look.

- Integrated manual focus achieve a perfect, clear gobo or a nice soft edge
- Adjustable yoke mount fixture where you want it even when headroom is limited.
- Available in black or white the perfect body color for your application.

For detailed product information, please refer to the Product Guide at https://www.vari-lite.com/global/products/acclaim-led-ple-ww





# Specifications

Due to continuous improvements and innovations, specifications may change without notice.

#### Source

LED	Monochromatic Light Engine
Source Max Power Consumption	165 W
Source CCT	3200 K
LED Refresh Rate	500 Hz to 4000 Hz
Dimming	Electronic 8-bit / 16-bit, Local
Dimmer Curves	Square Law (Default), Linear, S -Curve
Strobe Speed	0 - 30Hz

#### Optical Performance

Engine only - 8,500
3200 K
95
Rf 91 / Rg 96
93
95

#### **Imaging**

Shutter	4 blade manual framing shutters

#### **Electrical**

Output Power Consumption	195 W
Power Connection	TrueOne Compatible - In / Thru
	Power cable not included - input connector only
Input Voltage	100-240 VAC, 50 / 60 Hz
Standby Power	10 W

#### Data

Supported Protocols	DMX512-A (RDM)
DMX Modes	
16-Bit	3 Channels
8-Bit	2 Channels
Data Connections	5 - Pin XLR Input and Thru

## Noise Level / Fan Control (Base Level 21 dB @ 1 m (3.3

ft))

//	
Standard Mode	43.9 dB
Studio Mode	35.9 dB
Whisper Mode	32.7 dB
Fan Mode	Continuous (On) / Auto Ramping
Fan Level Preset	Standard, Studio, Whisper
Cooling System Type	Forced Air Cooling


#### Mounting


Yoke	Double clutch locking yoke >270° Swivel Yoke M12
	(1/2") Centre hole
Fixture mounting/Hanging	Hanging - Floor - Side
orientation	
Secondary Safety Wire Point	1 x Safety point located on rear of fixture housing
	Safety Wire not included

#### Photometrics and IES Files

For IES files and photometric reports, please refer to the product page: https://www.vari-lite.com/global/products/acclaim-led-ple-ww

## **Dimensions**





LT SERIES	ORDER CODE
PLT 10° lens tube black	64010-002
PLT 10° lens tube white	64010-102
PLT 14° lens tube black	64010-003
PLT 14° lens tube white	64010-103
PLT 19° lens tube black	64010-004
PLT 19° lens tube white	64010-104
PLT 26° lens tube black	64010-005
PLT 26° lens tube white	64010-105
PLT 36° lens tube black	64010-006
PLT 36° lens tube white	64010-106
PLT 5° lens tube black	64010-001
PLT 5° lens tube white	64010-101
PLT 50° lens tube black	64010-007
PLT 50° lens tube white	64010-107
PLT 70° lens tube black	64010-008
PLT 70° lens tube white	64010-108
PX ZOOM SERIES	ORDER CODE
25°-50° zoomspot lens tube black	SPX2550LT
15°-35° zoomspot lens tube black	SPX1535LT
PX FIXED	ORDER CODE
14° fixed beam lens tube black	SPX14LT
19° fixed beam lens tube black	SPX19LT
26° fixed beam lens tube black	SPX26LT
36° fixed beam lens tube black	SPX36LT
50° fixed beam iens tube black	SPX50LT
ENS HOLDERS/ADAPTERS/GEL FRAMES	ORDER CODE
PLT FIXED LENS, 4 - Lug lens tube adapter; for use with ACCLAIM PLE, and LEKO LED Light sources, Black	64010-012
PLT FIXED LENS, $4$ - Lug lens tube adapter, for use with ACCLAIM PLE, and LEKO LED Light sources, White	64010-112
Universal tube adapter black	PLPF4ULTA
Color Frame Kit, PLT Lens Tube 10 x Gel Frame 5° Black	64010-909
Color Frame Kit, PLT Lens Tube 10 x Gel Frame 10°, 14°, 19°, 26° Black	64010-910
Color Frame Kit, PLT Lens Tube 10 x Gel Frame 36°, 50°, 70° Black	64010-911

#### **Physical**

Construction	Machined aluminum, sheet metal, and molded engineering
	grade plastic components
IP Rating	IP20
Standard Finish	Black, White
Dimensions	190 x 283 x 268 mm (8.0 x 11.0 x 11.0 in)
Dimension (w/ yoke)	398 x 268 x 268 mm (15.0 x 11.0 x 11.0 in)
Fixture Weight	6.0 kg (13.0 lb)
Operating	-10-40°C (14-104°F)
Temperature	

### **Certification and Safety**

Approbation

ETL (UL & CSA)CB/IECEE Scheme for CE-LVD, FCC, ICES, RCM, CE-EMC, UKCA, RoHS, ISO 9001

#### Gobo and Effect Wheels

Gobo Gate	B size (holder optional accessory)
Gobo Size	В

### Luminaire and Accessories

Product type	Order Code
VL600 ACCLAIM PLE WW, Black	64511-006
165W Monochromatic Light Engine - WW, c/w Power input connector, Black	
VL600 ACCLAIM PLE WW, White	64511-106
165W Monochromatic Light Engine - WW, c/w Power input connector, White	
	64511-012
VL600 Acclaim B Size gobo holder	64511-012
Accessories  VL600 Acclaim B Size gobo holder  VL600 ACCLAIM ZOOMSPOT/PLE, B Size Adjustable Gobo Holder - Metal or Glass images  VL600 Acclaim IRIS	64511-012 64511-013

