

PRO X20

2 BALANCED ARMATURE DRIVERS

PROFESSIONAL IN-EAR MUSICIANS' MONITORS

The Pro X redefines and elevates the UM Series with more efficient sound channels that provide cleaner and better frequency responses with the most ergonomic fit in the industry.

LOW

MID

HIGH

OVERVIEW:

The Pro X20 features two proprietary balanced-armature drivers, with a two-way passive crossover. Developed to reproduce a large and enveloping sound, the Pro X20 has the range and output for any stage condition. The dual balanced-armature driver design delivers robust low end and crystal clear highs, with all the detail and nuance that professional musicians have come to expect from a Westone Audio in-ear monitor.

IDEAL FOR:

On-Stage Monitoring, Vocalists, Guitar Players, Keyboard Players, Drummers & Sound Engineers



TECH SPECS

SENSITIVITY: 119 dB @ 1mW

FREQ. RESPONSE: 20Hz - 18kHz

IMPEDANCE: 27 ohms

DRIVER: Dual Balanced Armatures with passive crossover

IN THE BOX

IN-EAR MONITORS

Pro X20 Universal-Fit In-Ear Musician's Monitors

CABLE: Linum Bax T2™ Detachable Cable

TIPS: 5 Pair Foam + 5 Pair Silicone

ACCESSORIES:

Impact Resistant Monitor Vault



ERGONOMIC TECHNOLOGY

60 years of experience designing products for the ear, has resulted in a universal-fit earpiece that is compact, low-profile, lightweight, and extremely comfortable. Our proprietary ear tips enhance the performance of the Pro X20 by ensuring a great fit and seal, right out of the box.



BALANCED-ARMATURE DRIVER

Westone Audio's proprietary balanced-armature drivers provide enhanced sonic detail and frequency range that extends well beyond other in-ear solutions.



LINUM BAX T2™ DETACHABLE CABLE

High-strength, ultra-low resistance 84 strand Silver plated copper litz wires, low microphonics, low crosstalk, with the most advanced and robust audio connector available in the industry.



PRECISE ACOUSTIC SYMMETRY

Left and right earpiece responses are matched to an extraordinarily tight +/- 2dB tolerance. This extends well beyond typical in-ear solutions.