

VM-24H

2x1:4 HDMI Distribution Amplifier













The VM-24H is a distribution amplifier for HDMI signals. The unit reclocks and equalizes one of two selectable input signals and distributes it to four identical outputs.

FEATURES

- Max. Data Rate 6.75Gbps (2.25Gbps per graphic channel).
- HDTV Compatible.
- HDCP Compliant.
- HDMI Support Deep Color, x.v.Color™, Lip Sync, CEC.
- 3D Pass-Through.
- I-EDIDPro™ Kramer Intelligent EDID Processing™ Intelligent EDID handling & processing algorithm ensures Plug and Play operation for HDMI systems.
- Active Output LED Indicators.
- Control Front panel, RS-232, IR switching.
- Worldwide Power Supply 100-240V AC.
- Standard 19" Rack Mount Size 1U. Rack "ears" included.

TECHNICAL SPECIFICATIONS

INPUTS: 2 HDMI connectors.

OUTPUTS: 4 HDMI connectors.

BANDWIDTH: 6.75Gbps (2.25Gbps per graphic channel).

COMPLIANCE WITH HDMI

STANDARD:

Supports HDMI and HDCP.

CONTROLS: EDID SELECT, EDID READ, IN 1, IN 2 buttons, RS-232, IR.

INDICATOR LEDs: Output status LEDs.

POWER CONSUMPTION: 100-240V AC, 50/60Hz, 16VA.

DIMENSIONS: 19" x 7" x 1U W, D, H, rack mountable.

WEIGHT: 2.5kg (5.5lbs) approx.

INCLUDED ACCESSORIES: Power cord, null-modem adapter, Windows®-based control software, IR remote

control.

OPTIONS: External remote IR receiver cable.

