

**NEW!**

# SERIES8

## Robust Miniature Microphones

Choose **OMNIDIRECTIONAL** or **CARDIOID** in headset, earworn and lavalier styles with a performance boost up to 148dB SPL.



HEADSET



EARWORN



LAVALIER



CELEBRATED "UNBREAKABLE BOOM"



WATER, SWEAT AND MAKEUP PROOF



X-CONNECTORS: REPLACE AS NEEDED



tiny but  
**TOUGH**

**SERIES8** mics are tiny but tough, which makes them an easy choice for delivering an epic performance in broadcast or live production.

[www.point-sourceaudio.com](http://www.point-sourceaudio.com)

The more you know, the better we sound.

# MICROPHONE COMPARISON CHART


**NEW!**



## PERFORMANCE VOCALS


## OPTIMIZED SPEECH

## BASIC VOICE




Omni

**CO-8W**



Cardioid

**CR-8**




Omni

**CO-6**



Omni

**CO-5W**



Omni

**CO-3**

### PREMIUM FEATURES

<b>Maximum SPL</b>	148dB SPL	135dB SPL	125dB SPL	125dB SPL	116dB SPL
<b>"Unbreakable Boom"</b>	•	•	•		
<b>Water, sweat, makeup Proof</b>	•			•	
<b>Interchangeable Connectors</b>	•	•			
<b>STYLE OPTIONS</b>					
<b>Headset</b>	•	•			
<b>Earset KIT</b>	•	•	•	•	•
<b>Earworn</b>	•	•	•	•	•
<b>Lavalier</b>	•	•			
<b>EARWORN PLACEMENT</b>					
<b>Left Ear</b>	•	•	•	•	•
<b>Left or Right Ear</b>	•	•	•	•	
<b>COLOR OPTIONS</b>					
<b>Beige</b>	•	•	•	•	•
<b>Black</b>	•	•	•		•
<b>SPECIFICATIONS</b>					
<b>Element</b>	Back Electret Condenser	Back Electret Condenser	Back Electret Condenser	Back Electret Condenser	Back Electret Condenser
<b>Pattern</b>	Omni-directional	Uni-directional	Omni-directional	Omni-directional	Omni-directional
<b>Frequency</b>	30 Hz - 18kHz	100 Hz - 12kHz	40 Hz - 17kHz	40 Hz - 17kHz	50 Hz - 16kHz
<b>Sensitivity</b>	-48dB ± 3 dB (0dB = 1V/microbar at 1kHz)	-69dB ± 3 dB (0dB = 1V/microbar at 1kHz)	-67dB ± 3 dB (0dB = 1V/microbar at 1kHz)	-67dB ± 3 dB (0dB = 1V/microbar at 1kHz)	-60dB ± 3 dB (0dB = 1V/microbar at 1kHz)
<b>Output Impedance</b>	3,000 Ω (at 1kHz)	1,700 Ω (at 1kHz)	2,000 Ω ± 30% (at 1kHz)	2,000 Ω ± 30% (at 1kHz)	1,500 Ω ± 30% (at 1kHz)
<b>Operating Voltage</b>	1.5 - 5VDC	1.5 - 5VDC	1.5V - 10VDC	1.5V - 10VDC	1.5V - 10VDC
<b>Cable Length</b>	4 ft .077 in. + connector	4 ft .077 in. + connector	4 ft 2 in. + connector	4 ft 2 in. + connector	3 ft 11 in. + connector
<b>Net Weight</b>	0.6 oz	0.6 oz	0.6 oz	0.6 oz	.28 oz
<b>Maximum SPL</b>	148dB SPL	135dB SPL	125dB SPL	125dB SPL	116dB SPL
<b>Standard Accessories</b>	Windscreens, cable clip, storage box	Windscreens, cable clip, storage box	Windscreens, cable clip, storage box	Windscreens, cable clip, storage box	Cable clip, storage box