


# SOLLA Flood Light Instruction

## Technical Parameters:

Power	30W/60W/100W/150W/200W/300W/400W/500W/600W
Luminous Flux	2400lm/ 4800lm/ 8000lm/ 12000lm/16000lm/24000lm/ 32000lm/40000lm /48000lm
Led Beads Quantity	36pcs/72pcs/144pcs/216pcs/288pcs/420pcs/560pcs/700pcs/854pcs
Product Weight	1.78lb/2.84lb/3.59lb/5.06lb/6.67lb/10.86lb/13.10lb/18.4lb/20.1lb
Power Factor	≥0.90
CRI	≥70
Voltage	AC100-120V
Color Temperature	3000K/6000K ±300
Beam Angle	140°
Working Temperature	-20~+55°C /-4~+131°F
Protection Class	IP66
Efficacy	80LM/W
Material	Die-cast aluminum , Tempered Glass

## Size:

30W	60W	100W	150W	200W	300W	400W	500W	600W
8.5x8.1x1.6 Inches	10.5x9.7x1.6 Inches	12.3x10.7x1.8 Inches	14.6x11.5x2.0 Inches	16.5x12.6x2.0 Inches	18.5x14.0x2.7 Inches	20.0x15.0x3.0 Inches	21.5x17.5x3.7 Inches	22.3x17.5x4.1 Inches



1. Waterproof Joint
2. Die-casting Aluminum Convection Fin Type Heat Sink
3. Adjustable Mounting Bracket: 180°
4. Hi-Q SMD LED Chips
5. Waterproof & Dustproof Tempered Glass

If there is any question, please contact our customer service team at: [vip@solla.us](mailto:vip@solla.us).