



We Compress For Less ☆ www.CompressedAirUSA.com

GEAR-XL-S

Standard Gear Oil

GEAR-XL-S is a mineral-based extreme pressure (EP) gear lubricant. It is formulated to enhance protection in applications requiring heavy load carrying capabilities. GEAR-XL-S can be used for lubrication of heavily loaded enclosed gear sets and in some worm gear applications.

ATTRIBUTES:

- Protects against wear
- Long fluid life
- Excellent oxidative resistance
- High flash point 495°F

LUBRICANT PROPERTIES:

▪ GEAR-XL-S Grade	TEST METHOD	220
▪ Viscosity cSt @ 104°F	ASTM D7042	206.2
▪ Viscosity cSt @ 212°F	ASTM D7042	20.3
▪ Viscosity Index	ASTM D2270	117
▪ Flash Point °F/°C	ASTM D92	495/257
▪ Pour Point °F/°C	ASTM D5949	10/-12
▪ Copper Corrosion, 24 hr	ASTM D130	1a
▪ Rust Test	ASTM D665	Pass
▪ Demulsibility, 130°F, 30 min	ASTM D1401	40/39/1
▪ Four Ball Wear Diameter, mm	ASTM D4172	0.45
▪ FZG	ASTM D5182	11