



We Compress For Less ☆ www.CompressedAirUSA.com

HYDRA-AW-32

Anti-Wear Hydraulic Fluid

HYDRA-AW-32 is an anti-wear hydraulic fluid designed for use in various hydraulic applications and provides good wear protection, oxidation and corrosion control, as well as foam suppression and demulsibility. HYDRA-AW-32 is non toxic to aquatic life and meets or exceeds the EPA LC 50 test.

ATTRIBUTES:

- High flash point (425°F)
- Superior pump protection
- Protects against wear, rust, and corrosion
- Readily separates from water
- Foam suppression
- Non-Toxic, Non-Hazardous

LUBRICANT PROPERTIES:

▪ HYDRA-AW-32 Grade	32
▪ Viscosity cSt @ 104°F	32.8
▪ Viscosity cSt @ 212°F	5.5
▪ Viscosity Index	103
▪ Flash Point °F/°C	425/218
▪ Pour Point °F/°C	-16/-27
▪ Four Ball, 40 kg, 1200 RPM, 167°F, 1 hr, Scar Diameter mm	.51
▪ Copper Corrosion, 24 hr	1b
▪ Rust Test	Pass
▪ Demulsibility, 130°F, 30 Min	40/40/0
▪ RPVOT, 25.4 PSI Drop, Min	219