



We Compress For Less ☆ www.CompressedAirUSA.com

RECIP-XL-HPBA

High Pressure Breathing Air Reciprocating Air Compressor Lubricant

Designed to lubricate breathing air compressors, RECIP-XL-HPBA is diester based and provides exceptional carbon resistance in high-temperature/high-pressure compressors. It's extremely low volatility, excellent hydrolytic stability and very high flash point contribute to safer operation. With its advanced additive system, RECIP-XL-HPBA also provides extraordinary wear protection.

ATTRIBUTES:

- Designed specifically for high-pressure breathing air compressors
- Controls carbon and varnish formation
- Protects against rust and corrosion
- Long oil life
- High flash and auto-ignition points for added safety
- Good film strength and anti-wear properties
- Non-toxic and Non-hazardous

LUBRICANT PROPERTIES:

| | |
|-------------------------------|---------|
| ▪ RECIP-XL-HPBA Grade | 100 |
| ▪ Viscosity cSt @ 104°F | 101 |
| ▪ Viscosity cSt @ 212°F | 11.5 |
| ▪ Viscosity Index | 101 |
| ▪ Flash Point °F/°C | 500/260 |
| ▪ Pour Pont °F/°C | -35/-37 |
| ▪ Copper Corrosion, 24 hr | 1a |
| ▪ Demulsibility, 130°F, 30min | 40/38/2 |