



We Compress For Less ☆ www.CompressedAirUSA.com

RECIP-XL-FG

Food Grade Reciprocating Air Compressor Lubricant

RECIP-XL-FG synthetic food-grade air compressor lubricant contains high-performance fluids and is designed for extended drain intervals.

This lubricant meets H1 requirements for lubricants with incidental food contact (FDA 21 CFR 178.3570), and meets NSF requirements.

ATTRIBUTES:

- 4000-6000 hours of oil life at 212°F discharge temperature
- Meets H1 requirements for incidental food contact (FDA 21 CFR 178.3570)
- Meets NSF requirements
- Oxidatively stable
- Resists water contamination
- Protects against rust and corrosion
- Controls carbon and varnish formation
- Protects against wear
- Low volatility
- Excellent film strength
- High flash point 498°F
- Non-toxic and Non-hazardous

LUBRICANT PROPERTIES:

▪ RECIP-XL-FG Grade	100
▪ Viscosity cSt @ 32°F	1703
▪ Viscosity cSt @ 104°F	103
▪ Viscosity cSt @ 140°F	41.7
▪ Viscosity cSt @ 176°F	21.0
▪ Viscosity cSt @ 212°F	11.9
▪ Flash Point °F/°C	498/259
▪ Copper Corrosion, 24 hr	1a
▪ Demulsibility, 130°F, 30min	40/40/0
▪ Rust Test: Distilled Water	Pass
▪ Rust Test: Salt Water	Pass
▪ Foam Sequence I, II, III	0/0/0