



We Compress For Less ☆ [www.CompressedAirUSA.com](http://www.CompressedAirUSA.com)

## VAC-XL-FG

### Food Grade Vacuum Lubricant

VAC-XL-FG is designed to provide excellent service and a long life in vacuum pumps. It has a very low vapor pressure, very high oxidative resistance, and excellent thermal and shear stability. VAC-XL-FG protects against wear, rust, and corrosion. VAC-XL-FG's advanced-technology additive system protects vacuum pumps from varnish, carbon, and sludge deposits. This lubricant meets H1 requirements for lubricants with incidental food contact (FDA 21 CFR 178.3570), and meets NSF requirements. It also exceeds the requirements of DIN 51506 VD-L.

#### ATTRIBUTES:

- Meets H1 requirements for incidental food contact (FDA 21 CFR 178.3570)
- Meets NSF requirements
- Carbon, varnish, and wear control
- Excellent film strength
- Low vapor pressure
- Thermal, chemical, and oxidative stability
- Low volatility
- High flash point 399°F
- Non-toxic and Non-hazardous

#### LUBRICANT PROPERTIES:

▪ <u>VAC-XL-FG Grade</u>	<u>22</u>
▪ Viscosity cSt @ 104°F	23
▪ Viscosity cSt @ 212°F	4.47
▪ Flash Point °F/°C	399/204
▪ Copper Corrosion, 24 hr	1a
▪ Rust Test: Distilled Water	Pass
▪ Rust Test: Salt Water	Pass