



TOP FEATURES















































SPECIFICATIONS

6 INCH LED

SQUARE | FIRE RATED | CANLESS | RECESSED DOWNLIGHT

NW-P-SQDL-6-15W-5CT-FR-WH

NuWatt Fire Rated Ultra-Thin light is an all-in-one solution, eliminating the need for additional housing like fire rated cans or tenmat light covers. With reinforced fire-resistant steel casing our light passes UL263, ASTM E119, & CAN ULC S101 certifications, which provides a 2-hour fire rating, reducing costs and installation time.



TECHNICAL SPECS

VOLTAGE AC 120V WATTAGE 15W POWER FACTOR >0.9 LUMENS -----1200 CRI 90 EQUIVALENCY -----75/100

DIMMABLE: TRIAC DIMMING

110° BEAM ANGLE EFFICACY (LM/W) - - -70

COLOR TEMPERATURE 5CCT COLOR FIELD SELECTABLE •••••

2700K | 3000K | 3500K | 4000K | 5000K

OPERATING TEMPERATURE -----(-4°F~104°F) -20~40°C

IP RATING IP54

MOISTURE RATING WET LOCATION



WARRANTY -**5 YEAR WARRANTY** LIFETIME HOURS 50,000 HOURS

CONSTRUCTION

HOUSING MATERIAL STEEL BACK + HIGH TEMPERATURES RED PAINT

TRIM MATERIAL **DIE-CAST ALUMINUM**

PRODUCT WEIGHT-0.709 KG

PRODUCT DIMENSIONS 6.87 IN. X 6.87 IN. X 1.3 IN.

LENS DIAMETER 3.87 IN. X 3.87 IN.

LENS MATERIAL NON-YELLOWING ACRYLIC










TECHNICAL

6 INCH | SQUARE | FIRE RATED | CANLESS | RECESSED DOWNLIGHT

NW-P-SQDL-6-15W-5CT-FR-WH



IN STORE DISPLAY











PALLET