LODES

Nautilus, *design by* Andrea Tosetto, 2017

Wall

Strong design and leading—edge technology come together in this family of lamps characterised by a convex lens that projects the LED light wherever its needed or most preferred, for a truly efficient and personalised result. Versatile and dynamic, either on the wall, ceiling or suspended in a variety of versions and finishes, Nautilus lamps satisfy a full range of lighting needs, whether functional or purely decorative, in both residential and professional contexts.



Nautilus Wall	Light source	Frame Aluminium	Diffuser: Aluminium	Code
		Matte White 9010	Matte White 9010	165051
	LED	() Chrome	Matte White 9010	165006
	• 3000 K	() Chrome	Chrome	165008
	2 x 15W 2550 lm220-240V	() Chrome	Gold	165009
	CRI 90MacAdam 3-Step	() Chrome	Rose Gold	165010
	LED and driver included	Matte Black 9005	Matte Black 9005	165052
		() Chrome	Matte Black 9005	165007
		Matte Champagne	Matte Champagne	165053
		Matte White 9010	Matte White 9010	165048
	LED	Chrome	Matte White 9010	165001
	• 2700 K	() Chrome	Chrome	165003
	2 x 15W 2400 lm220-240V	() Chrome	Gold	165004
	CRI 90MacAdam 3-Step	() Chrome	Rose Gold	165005
	LED and driver included	Matte Black 9005	Matte Black 9005	165049
		Chrome	Matte Black 9005	165002
		Matte Champagne	Matte Champagne	165050

LODES

Nautilus Mini		Light source			Frame Metal			Diffuser: Aluminium		Code
		LED 2700 K 2 × 6W 816 lm 220-240V CRI 90 MacAdam 3-Step LED and driver included		Matte Black 9005			5	_		165042
				Matte White 9010				_		165041
		LED • 3000 K • 2 × 6W 840 lm • 220-240V		Matte White 9010				_		165046
		CRI 90 MacAdam 3-Step LED and driver included		Matte Black 9005			5			165047
Net weight: 0.75 kg	Gross weight: 0.95 kg	Parcels: N°1	Volume: 0.008 m³	7		C€	ERC	IP20	Energy Saving (\$	Dim Triac 🗒

Polar diagram

C0-C180 / C90-C270 cd/1000lm

Nautilus Wall


- LED 3000 K
- 2 × 6W | 840 lm 220-240V
- CRI 90
- MacAdam 3-Step

LED and driver included

- LED
 2700 K
 2 × 6W | 816 lm
 220-240V
- CRI 90
- MacAdam 3-Step

LED and driver included

Nautilus Mini Polar diagram



LED

- 3000 K 2 × 6W | 840 lm 220-240V
- CRI 90
- MacAdam 3-Step

LED and driver included

- LED
 2700 K
 2 × 6W | 816 lm
- 220-240V
- CRI 90
- MacAdam 3-Step

LED and driver included

Other applications of Nautilus





Ceiling

Suspension