



LABELMATE USA

PHYSICAL

OMNI-CAT	6	8	10	1-INCH	ACH
Height (in):	13.5 (343-mm)				
Width (in):	12 (305-mm)				
Depth (in):	15 (381-mm)	17 (432-mm)	18.5 (470-mm)	15 (381-mm)	
Weight (lbs):	23 (10.5-kg)	24 (11-kg)	25 (11.5-kg)	21 (9.5-kg)	24 (11-kg)

TECHNICAL

Max Roll Diameter (in):	12 (305-mm)				
Core Diameter (in):	3 (76-mm)			1 (25-mm)	1 - 4 (25-101mm)
Max Material Width (in):	6.5 (165-mm)	8.5 (216-mm)	10.5 (267-mm)	6.5 (165-mm)	
Max Roll Weight (lbs):	35 (16-kg)				30 (14-kg)
Max Speed (in/sec):	300 (7620-mm)				
Min Speed (in):	0.5 (13-mm)				
Max RPM:	485				
Max Torque (Nm):	1.62				
Guide Flanges:	2				1

ELECTRICAL

Power Adaptor:	PS-65
Input:	100 - 240VAC ~ 47-63Hz 1.6A
Output:	19VDC ~ 6.3A 120W



OMNI-CAT WINDERS

702.435.8535
sales@labelmateusa.com
labelmateusa.com

