

LD-300 SERIES LABEL DISPENSERS

LABELMATE USA Label Dispensers are the highest-quality, easiest to use, most durable and reliable Label Dispensers available. The simple to adjust Reflective Sensor technology utilized by the Dispensers makes it extremely easy to adjust for any label length. As you pick up one label the next one is immediately advanced. The labels are presented at the front of the machine, which is convenient for both left-handed and right-handed operators. Stainless Steel models are available for clean environments.



LD300-RS-SS

Technical Specifications	LD-300-RS-SS	LD-300-U-SS
Construction	Stainless Steel	
Max Label Width (in)	8.5 (218-mm)	
Min Label Width (in)	2 (50-mm)	
Max Label Length (in)	N/A	
Min Label Length (in)	1 (25-mm)	
Label Types	Opaque	Transparent & Opaque
Max Roll Diameter (in) ¹	8.6 (220-mm)	
Core Diameter (in)	1.5 or Larger (38-mm)	
Max Speed (ips)	8 (203-mm)	
Dimensions-HWD (in)	14 x 12 x 10 (355 x 305 x 254-mm)	
Weight (lbs)	20 (9-kg)	
Power Specifications	120 - 240 VAC in, 15VDC 3A Out	
Warranty	3 Year Limited Warranty on Label Dispenser; 1 Year Limited Warranty on Power Adaptor	
Available Options	<ul style="list-style-type: none"> • BP-LD (Mobile Battery Pack & Charger) • LRB-12 (Label Roll Bracket Extension) • FLANGES-LD (Supply Roll Flange Plates) 	

1. LRB-12 increases Maximum Supply Roll Diameter to 12" (305-mm).