

## CAT-3SA-ACH

### CAT-3SA-1-INCH • CAT-3SA-CORELESS

The CAT-3SA-SPECIALTY Rewinder Series provides the ability to load and wind onto non-standard diameter cores through the use of Fin-Style and Adjustable Core Holders. These Rewinders are ideal for use in-line with a printer because they feature a special Sensor Arm that automatically mirrors the start/stop action of the printer to prevent excessive tension on the label web.



**CAT-3SA-ACH**

Technical Specifications	CAT-3SA-1 INCH	CAT-3SA-ACH	CAT-3SA-CORELESS
<b>Max Roll Diameter (in)</b>	12 (305-mm)	11 (279-mm)	12 (305-mm)
<b>Core Diameter (in)</b>	1 (25-mm)	1 - 4 (25 - 102-mm) <sup>1</sup>	N/A
<b>Max Media Width (in)</b>	6 (152-mm)		
<b>Max Roll Weight (lbs)</b>	20 (9-kg)	17 (8-kg)	20 (9-kg)
<b>Dimensions-HWD (in)</b>	14 x 17 x 17 (356 x 432 x 432-mm)		
<b>Weight (lbs)</b>	26 (11.8-kg)	28 (12.7-kg)	26 (11.8-kg)
<b>Max Speed (ips)</b>	120 (3048-mm)	115 (2921-mm)	120 (3048-mm)
<b>Min Speed (ips)</b>	1 (25-mm)		
<b>Max Torque (in-oz) <sup>2,3</sup></b>	183		
<b>Max RPM <sup>2</sup></b>	388		
<b>Number of Flanges</b>	2	1	2
<b>Power Specifications <sup>2</sup></b>	120 - 220VAC in, 12VAC 40W Out		
<b>Warranty</b>	5 year limited warranty on Rewinder - 1 year limited warranty on Power Adaptor		
<b>Available Options</b>	<ul style="list-style-type: none"> <li>• HTO-CAT (Hi-Torque Option)</li> <li>• LTO-CAT (Lw-Torque Option)</li> <li>• FOOTSWITCH</li> </ul>	<ul style="list-style-type: none"> <li>• APG-CAT (Paper Guide)</li> <li>• HTO-CAT (Hi-Torque Option)</li> <li>• LTO-CAT (Lw-Torque Option)</li> <li>• FOOTSWITCH</li> </ul>	<ul style="list-style-type: none"> <li>• HTO-CAT (Hi-Torque Option)</li> <li>• LTO-CAT (Lw-Torque Option)</li> <li>• FOOTSWITCH</li> </ul>

1. The **CAT-3-ACH** can also rewind corelessly

2. **HTO-CAT** increases Max Torque to 228 in-oz, Max RPM to 485, 304 ips (7,721-mm), and Power Out to 19VDC 80W.

3. **LTO-CAT** decreases Torque Range to 172 - 35 in-oz.