



**Cambridge**  
materials testing limited


6991 Millcreek Drive, Unit 13  
Mississauga, Ontario L5N 6B9  
Tel: (905) 812-3856 Fax: (905) 812-3866  
[www.cambridgematerials.com](http://www.cambridgematerials.com)

---

Laboratory # 889966-22  
Prescient-X

**BACTERIA FILTRATION EFFICIECNY**

The results of this test are detailed in the report from GAP Labs, under GAP Project Number: A15692-3225, which is attached below.



1020 Hargrrieve Rd, Unit 14  
London, Ontario, Canada N6E 1P5  
Telephone: (519) 681-0571  
Fax: (519) 681-7150  
Email: info@gaplab.com  
Website: www.gaplab.com

Date: 20-Jun-22	GAP Project Number: A15692-3225
<b>Report to:</b> Cambridge Materials Testing Ltd. Attn: Rany El-Roz 13-6991 Millcreek Drive Mississauga, ON L5N 6B9 Tel: 905-812-3856 Fax: Email: ranyel-roz@cambridgematerials.com	
GAP Sample Number: 3225 Test Article: 889966 Received Date: 15-Jun-22 Test Date: 16-Jun-22 Challenge Microbe: <i>Staphylococcus aureus</i> ATCC 6538 Test Side: Thicker side facing challenge. Area Tested: ~38.5 cm <sup>2</sup> Flow Rate: 28.3 LPM Test Article Conditioning: 85 ± 5% RH at 25.0 ± 0.5°C for a minimum of 4 hours	

**ASTM F2101-19: Standard Test Method for Evaluating the Bacterial Filtration Efficiency (BFE) of Medical Face Mask Materials, Using Biological Aerosol of Staphylococcus aureus**

A Bacterial Filtration Efficiency (BFE) test was completed according to the procedure in ASTM F2101 to determine the filtration efficiency of test articles by comparing the bacterial control counts upstream of the test article to the bacterial counts recovered downstream. A suspension of *S. aureus* was aerosolized using a nebulizer and delivered to the test article at a constant rate with a target delivery rate of  $1.7 \times 10^3 - 3.0 \times 10^3$  colony forming units (CFU) per test article with a mean particle size (MPS) of  $3.0 \pm 0.3 \mu\text{m}$ . The aerosolized suspension was drawn through the test article which was clamped in a six stage Andersen air sampler, at a constant flow rate of 28.3 liters per minute (LPM), for collection on bacteriological agar plates.

Challenge Level (Positive Control):  $2.2 \times 10^3$  CFU

Mean Particle Size of Challenge:  $3.1 \mu\text{m}$

Negative Control Count: <1 CFU

**Results:**

Test Article	Total CFU Recovered	Bacterial Filtration Efficiency (%)
1	<1	>99.9%
2	3	99.9%
3	<1	>99.9%
4	3	99.9%
5	3	99.9%





1020 Hargrrieve Rd, Unit 14  
London, Ontario, Canada N6E 1P5  
Telephone: (519) 681-0571  
Fax: (519) 681-7150  
Email: info@gaplab.com  
Website: www.gaplab.com

Date: 20-Jun-22 GAP Project Number: A15692-3225

$$\% BFE = \frac{C - T}{C} \times 100$$

Where: C = Challenge Level  
T = Total CFU recovered downstream of test article

$$MPS = \frac{(P1 \times C1) + (P2 \times C2) + (P3 \times C3) + (P4 \times C4) + (P5 \times C5) + (P6 \times C6)}{C1 + C2 + C3 + C4 + C5 + C6}$$

Where: Px = 50% effective cut-off diameter for the x<sup>th</sup> stage as indicated by the manufacturer  
Cx = raw count (on stages 1 and 2) or the "probable hit" count determined using the positive hole conversion chart from the cascade impactor manual (for stages 3 through 6) on the x<sup>th</sup> stage.

Notes:

If you have any questions regarding the analysis please do not hesitate to contact the lab anytime at (519) 681-0571

Reported By: Shawn Verhoeven  
Position: Technical Manager


Manager Approval: Conrad Odegaard  
Position: Technical Manager

Signature: Sh Verhoeven

Signature: Conrad Odegaard

*These test results relate only to the samples submitted and the analyses requested.  
This test report cannot be reproduced except in full, without written permission from GAP.*





1020 Hargrrieve Rd, Unit 14  
London, Ontario, Canada N6E 1P5  
Telephone: (519) 681-0571  
Fax: (519) 681-7150  
Email: info@gaplab.com  
Website: www.gaplab.com

Date: 20-Jun-22

GAP Project Number: A15692-3225

### Appendix

**Table 1:** Raw counts from each stage of the 6 stage cascade air sampler as required in ASTM F2101 Section 14.8. The numbers presented for stage 1 and 2 represent the total bacterial colonies present and stages 3 through 6 represent a "positive-hole" count. For stages 3 through 6, the air flow through the impactor follows the jet pattern produced by the 400-holes present in these stages. As a result, the count must be corrected using a positive hole correction table based on the principle where the chance of a viable cell/particle impacting in a new, unoccupied, "jet" hole decreases as the total viable particles increase.

Stage Number	Test Article				
	1	2	3	4	5
1 - Raw Count	0	0	0	0	0
2 - Raw Count	0	0	0	0	0
3 - Positive Hole	0	0	0	0	1
4 - Positive Hole	0	1	0	0	0
5 - Positive Hole	0	2	0	3	2
6 - Positive Hole	0	0	0	0	0

**Table 2:** Counts obtained from each stage, including the "positive-hole" correction for stages 3 through 6

Stage Number	Test Article				
	1	2	3	4	5
1 - Raw Count	0	0	0	0	0
2 - Raw Count	0	0	0	0	0
3 - Positive Hole	0	0	0	0	1
4 - Positive Hole	0	1	0	0	0
5 - Positive Hole	0	2	0	3	2
6 - Positive Hole	0	0	0	0	0