



# AFFORDABLE AND RELIABLE

3 inch POS printer  
**SRP-330**



## HIGHLIGHTS



### Dual Communication Interface

- USB V2.0 FS + Ethernet
- USB V2.0 FS + Serial
- USB V2.0 FS + Parallel



### 2" or 3" Paper Choice

This two-in-one printer is equipped with a 2" partition, in which you can instantly change whether you desire 2 or 3 inch receipt. No need for utility or dip switch changes.



### Standard Printing Performance

- Printing speed up to 200 mm/sec



**BIXOLON**<sup>®</sup>  
a Better Solution for your Business<sup>™</sup>

# 3 inch POS Printer SRP-330



## SPECIFICATIONS

### Print Characteristics

**Print Method**  
Direct Thermal

**Print Speed**  
200 mm/sec

**Print Resolution**  
180 dpi

**Print Width**  
Up to 72 mm

**Sensor**  
Paper End, Cover Open

### Media Characteristics

**Media Type**  
Receipt

**Media Width**  
80 mm

**Media Roll Diameter**  
Up to 80 mm

**Media Thickness**  
0.062 ~ 0.075 mm

**Supply Method**  
Easy Paper Loading

### Physical Characteristics

**Dimensions (W x L x H)**  
153 x 195 x 145 mm  
(6.02 x 7.68 x 5.70 inch)

**Weight**  
1.44 kg (3.17 lbs.)

**Power**  
EnergyStar Certified,  
External Power Adaptor 100-240V AV, 50/60Hz

**Drawer Port**  
2 ports (via y-type adaptor)

### Performance Characteristics

**Memory**  
64 Mbit SDRAM, 16 Mbit FlashROM

**NV Image Memory**  
256 Kbytes (mono)

**Receive Buffer**  
4 Kbytes

**User Define Buffer**  
12 Kbytes

**Interface**  
Dual Interface  
USB V2.0 FS + Serial  
USB V2.0 FS + Parallel  
USB V2.0 FS + Ethernet

### Environment Characteristics

**Temperature**  
Operating: 0 ~ 45°C (32 ~ 113°F)  
Storage: -20 ~ 60°C (-4 ~ 140°F)

**Humidity**  
Operating: 10 ~ 80% RH  
Storage: 10 ~ 90% RH

### Reliability

**Printer Unit (MCBF)**  
60 Million Lines

**TPH**  
150 km

**Auto Cutter**  
1.5 Million Cuts

### Software

**Emulation**  
BXL / POS

**Driver / Utility**  
Windows Driver, OPOS Driver, JPOS Driver,  
Linux CUPS Driver, Mac Driver,  
Virtual COM USB/Ethernet Driver, Utility Program  
**SDK**  
Android SDK

### Fonts / Graphics / Symbologies

**Character Size**  
Font A: 12 x 24 Font B: 9 x 17  
Font C: 9 x 24  
KOR, CHN, JPN: 24 x 24

**Characters Per Line**  
Font A: 42 Font B, C: 56  
KOR, CHN, JPN: 21

**Character Sets**  
Alphanumeric: 95  
Extended Graphics: 128 x 37 page  
International: 32

**Graphics**  
Supporting user-defined fonts, graphics, formats,  
and logos

**Barcode Symbologies**  
1D: Coda Bar, Code39, Code93, Code128, EAN-8,  
EAN-13, ITF, UPC-A, UPC-E  
2D: PDF417, QR Code

### Accessories

**Optional**  
USB A-B cable, 2" partition, Splash proof cover,  
External buzzer, B-melodist (RMB-100)

BR-SRP-330-EN-MAR14

Copyright © BIXOLON Co., Ltd. All rights reserved.  
Features and specifications are subject to change without prior notice.

**BIXOLON®**

www.bixolon.com



#### BIXOLON Co., Ltd.

7-8F, (Sampyeong-dong), 20, Pangyoyeok-ro241beon-gil,  
Bundang-gu, Seongnam-si, Gyeonggi-do, 463-400, Korea (ROK)

Tel +82 (0) 31 218 5500

Fax +82 (0) 31 218 5589

E-mail sales@bixolon.com

#### BIXOLON America Inc.

3171 Fujita St Torrance,  
CA 90505, USA

Tel +1 858 764 4580

Fax +1 310 257 6869

E-mail sales@bixolonusa.com

#### BIXOLON Europe GmbH

Tiefenbroicher Weg 35,  
40472 Düsseldorf, Germany

Tel +49 211 68 78 54 0

Fax +49 211 68 78 54 20

E-mail sales@bixolon.de