

Mx915/Mx925 Protective Spill Cover Installation Instructions

CONGRATULATIONS!

You have made a great choice to protect your device from germs, spills and grime while extending the life of your Terminal/PIN Pad!

Instructions

- 1. Installation is easier if you take off the PINpad shield. This is done by sliding/pulling the shield down in the direction of the chip card reader. Do not lift it straight out/up. It is easiest if you slide it out with two hands on the rubber shield.**
- 2. Clean the keypad area so that it is free of dust and grime.**
- 3. Remove the white Mylar adhesive strips of the cover on all sides, taking care not to remove the sticky adhesive tape from the cover. THE DOUBLE SIDED TAPE WILL SOMETIMES STICK TO THE WHITE MYLAR. DON'T FRET. SIMPLY PLACE IT BACK ON THE COVER AND PEEL THE MYLAR OFF.**
- 4. Place over the keypad. Smooth down all sides and into the corners.**
- 5. If you took off the PINpad shield, now is the time to slide it back on.**
- 6. Check and smooth down any bubbles.**

And now your keys are protected!

Tips for Care and Use

**This cover is durable but it is made of plastic, so treat it gently.
Do not use sharp objects or pens as they may puncture the cover.
Clean with a damp cloth or antibacterial wipe. Do not remove the cover to clean it.**