

# Haugen

## Rotary Tillers

877-580-6218

### Skid-Steer Tillers



- Till forward or backwards
- Double Edge Replaceable Tine
- Tilling depth of 0-6 inches deep
- Skid Shoe Thickness 1/2" X 4"  
*Single Shoe Protects Motor & Controls Depth*
- The tiller is offset to the right hand side of your machine to cover the wheel tracks
- *Wire Guard To protect the motor and drive area*

	Tiller 52"	Tiller 68"	Tiller 76"
Working Width	52"	68"	76"
Over All Width	63"	79"	87"
# of Tines	28	36	40
Working Depth	0-6"	0-6"	0-6"
Tine Rotation	Bi-Rotational	Bi-Rotational	Bi-Rotational
Drive	Drive Direct	Drive Direct	Drive Direct
Hyd. Flow	Min/Max 18 / 35 GPM	Min/Max 18 / 35 GPM	Min/Max 18 / 35 GPM
Pressure Maximum	3500 Psi	3500 Psi	3500 Psi
Travel Direction	Forward / Reverse	Forward / Reverse	Forward / Reverse
Weight	450#	540#	630#



Marv Haugen Enterprises Inc.

P.O. Box 868 • Casselton, ND 58012 • Phone: 701-347-4827 • Fax: 701-347-4830

Website: [www.equipitnow.com](http://www.equipitnow.com) • E-mail: [haugen@equipitnow.com](mailto:haugen@equipitnow.com)