

WOOD guard® SWO

SWEDISH WOOD OIL™

ESPECIALLY FOR PRESSURE-TREATED WOOD



SUB-SURFACE LUBRICANT

**THE SUPERIOR PENETRATING TREATMENT IDEALLY SUITED FOR
TIMBERS, DECKS, DOCKS AND PILINGS**

KEEP OUT OF REACH OF CHILDREN

CAUTION

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

Manufactured for:

ISK Biocides, Inc.

416 East Brooks Road • Memphis, TN 38109

IBD-PL-1093A

10/12

Woodguard® is a registered trademark of IBC Manufacturing Company.
Swedish Wood Oil is a trademark of ISK Americas Incorporated.

MEETS ALL STATE VOC REQUIREMENTS
VOLATILE ORGANIC COMPOUNDS 224 grams/liter

WOODguard® SWO

THE SUPERIOR PENETRATING TREATMENT IDEALLY SUITED FOR TIMBERS, DECKS, DOCKS AND PILINGS

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUTION

May cause irritation to skin and eyes. Avoid contact with skin, eyes or clothing. Harmful if swallowed. Avoid breathing spray mist.

FIRST AID

| | |
|--------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| IF ON SKIN OR CLOTHING: | <ul style="list-style-type: none">• Take off contaminated clothing.• Rinse skin immediately with plenty of water for 15 – 20 minutes.• Call a Poison Control Center or doctor for further treatment advice. |
| IF IN EYES: | <ul style="list-style-type: none">• Hold eye open and rinse slowly and gently with water for 15 – 20 minutes.• Remove contact lenses, if present, after the first 5 minutes, then continue rinsing.• Call a poison control center or doctor for treatment advice. |
| IF INHALED: | <ul style="list-style-type: none">• Move person to fresh air.• If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible.• Call a Poison Control Center or doctor for further treatment advice. |
| IF SWALLOWED: | <ul style="list-style-type: none">• Call a poison control center or doctor immediately for treatment advice.• Have person sip a glass of water if able to swallow.• Do not induce vomiting unless told by a Poison Control Center or doctor.• Do not give anything by mouth to an unconscious person. |

HOT LINE NUMBER

In case of emergency, call Chemtrec toll free at 800-424-9300. Have the product container or label with you when calling a poison control center or doctor or going for treatment. Note to Physician: This product contains petroleum distillates.

PHYSICAL OR CHEMICAL HAZARDS

Combustible. Do not store or use near heat or open flame.

STORAGE AND DISPOSAL

Store in a secure, dry, well-ventilated area protected from extreme temperatures. Do not transfer to unmarked containers. Keep container tightly closed when not in use. Do not store with strong oxidizing agents such as peroxide. IF EMPTY: Do not reuse this container. Place in trash or offer for recycling if available. IF PARTIALLY FILLED: Call your local solid waste agency or 1-800-CLEANUP for disposal instructions. Never place unused product down any indoor or outdoor drain.

PRODUCT DESCRIPTION

Each changing season causes dimensional stresses that can splinter and physically damage a wooden deck or dock.

Developed in Sweden to protect "CCA" pressure treated wood from the harsh Nordic weather, WOODguard SWO repels water, promotes wood stability, and highlights natural wood tones. It allows the wood to weather naturally to a beautiful driftwood gray color.

Treated lumber (often green in color) is often prone to rapid moisture gains and losses that cause warping and splitting in many wood species.

WOODguard SWO is a heavy-duty, transparent treatment designed especially for protecting new, "pressure-treated" wood. It does not form a film and will never crack or peel.

WOODguard SWO is a water repellent wood stabilizer that beautifully highlights natural wood tones. WOODguard SWO retards cupping, warping and splitting and generally minimizes physical deterioration caused by dimensional instability resulting from water absorption and extreme humidity changes. WOODguard SWO treatment also helps reduce nail corrosion and popping.

DIRECTIONS FOR USE

Apply by spray, brush or roller. **One moderate coat is sufficient.** Surfaces should be clean and free of all loose debris. Test before using. Do not use on painted surfaces. Avoid contact with plants, shrubs and trees.

NEW DECKS & DOCKS: Allow the deck or dock to dry for two to three months. Sweep to remove dirt and debris before application.

WEATHERED, UNTREATED DECKS & DOCKS: Make sure surface is free of all dirt and debris. If a new appearance is desired, clean with a pressure washer to remove the gray surface of wood. After washing, let the wood surface dry for three days before applying WOODguard SWO.

WHEN PRESSURE WASHING: To avoid wood damage, and achieve maximum effectiveness, make sure the pressure is set below 500 psi, and keep the nozzle of the power washer approximately one foot from the surface.

Apply to dry wood for maximum penetration and fastest drying. Do not over apply.

1. **WOODguard SWO** penetrates into the wood with only a small portion evaporating. Do not apply to painted or otherwise sealed or highly dense surfaces. If in doubt, apply to a small test area. If the wood absorbs the treatment readily, it is suitable for use.
2. **WOODguard SWO** does not "DRY" in the conventional sense. It cures into the wood. Blot up any excess WOODguard SWO left unabsorbed on the surface.
3. Coverage 250 – 300 sq. ft / gallon, depending on surface condition and wood porosity.
4. Application temperature: Apply above 50°F. Hot weather promotes a faster cure time. Below 65°F, **WOODguard SWO** may become too viscous to spray.
5. **WOODguard SWO** softens asphalt (including asphalt shingles) – avoid contact.
6. Do not apply if rain is expected within 36 hours.
7. Avoid open flame during application and until the oil has thoroughly penetrated the treated surface.
8. Any subsequent coating applied over **WOODguard SWO** must be tested on a remote area to verify compatibility before application. **WOODguard SWO's** highly water repellent system will repel latex coatings and may not be compatible with some oil or alkyd coatings. **DO NOT TINT WOODguard SWO.**
9. Until **WOODguard SWO** has thoroughly cured, treated area may be slippery.
10. **WOODguard SWO** may be applied to newly-constructed, pressure-treated decks that are thoroughly dry. **Use only enough WOODguard SWO to be readily absorbed.**

CLEAN-UP: Use detergent and water on fresh **WOODguard SWO** coated brushes, etc. If it has had time to cure, mineral spirits or paint thinner may be used for clean up.

WARRANTY AND LIMITATION OF DAMAGES

Seller warrants to those persons lawfully acquiring title to this product that at the time of the first sale of this product by seller this product conformed to its chemical description and that it was reasonably fit for the purposes stated on the product label when used both in accordance with the Direction for Use appearing on the product label and under normal conditions of use. Buyers and users of this product assume the risk of all loss or damage from use or handling of this product that results from their failure to read and comply with the Directions for Use of this product which appear on the product label. SELLER MAKES NO OTHER EXPRESS OR IMPLIED WARRANTY, INCLUDING ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS OR OF MERCHANTABILITY, AND NO AGENT OF SELLER IS AUTHORIZED TO DO SO. Unless expressly prohibited by state law, the liability of seller for any breach of warranty shall not exceed the purchase price of the product as to which a claim is made.

Manufactured for:

ISK Biocides, Inc.

416 East Brooks Road • Memphis, TN 38109

IBD-PL-1093B

10/12