

# TECHNICAL SPECIFICATIONS



## G5 LIQUID SEALANT

REFERENCE: 143-0001



Sizes:

Gallons - Quarts - Pints - 8 oz  
3.748 ml. 948 ml. 473 ml. 236 ml.

### DESCRIPTION

**Symplex G5® Liquid Sealant**, Ultra Gloss long lasting Synthetic Protection, easy to apply and remove. Can be use in all kind of Paint, Glass, Stainless Steel, Chrome and Aluminum. Does not leave any white residue on plastic trims. G5 Liquid Gloss offers maximum UV protection to keep your vehicle's paint looking great for years

**DOES NOT STAIN ANY BLACK MOLDING TRIMS**

### PHYSICAL PROPERTIES

- Purple colored Liquid cream.
- Due to its chemical composition, the product tends to separate , shake well before using.
- Containers with plastic lids metered .
- It is applied by hand or with a foam.
- Does not stain the plastic exterior parts
- Product Life: 2 years.

### APPLICATION TECHNIQUES

The G5® , Ultra brightness was designed to facilitate and improve the quality of both enlisted vehicle paint shops and dealers.

SHAKE WELL BEFORE USING

- If applied manually, use a small amount in a special applicator Symplex P / N 111-0029 - UN or a microfiber cloth and lightly rub in a circular motion.
- Let dry approx. 60 seconds and remove with a clean cloth.
- For application with polishing machine , use a puff or foam pad Symplex Turbo P / N 133-0007 - A place a small amount and buff at low speed approx. 1200 rpm .

### CONTAINERS

8 oz containers. 16 oz. 32 oz. They are made of high strength PET . 128 oz container. (MPG) is produced in high density polyethylene (HDPE) It also provides a metering plastic cap in order to facilitate the closure of the container, preventing contamination, drying of the product, permit reopening, accurate and simple dosing.

### SPEED POLISHER / DA POLISHER

Most polishing machines found in workshops repair both electrical and pneumatic can be used with the XI Symplex® G5. A rotational speed between 1500 and 2000 rpm is recommended

### BUFFING & FINISHING PAD

Using Symplex® G5 with a Symplex® Turbo Extreme pad two faced (P/N 134-0007-UN), Piranha (P/N 134-0003-UN) o Flex (P/N 134-0004-UN). For additional Ultra gloss change to Symplex Turbo Foam Pad P/N 133-0007-UN

### HANDLING AND STORAGE

See the Safety Data Sheet (MSDS)

### PREVENTIVE INFORMATION

See product label and Material Safety Data Sheet for health and safety information before using this product.

### WARRANTY AND LIMITATION OF RESOURCES

Technical Information: The technical information, recommendations, and other statements contained in this document are based upon tests or experience that Symplex® considered reliable, but the accuracy of such information or exhaustive is not guaranteed.

Product Use: Many factors beyond the control of Symplex® and only the user's knowledge and control can affect the use and performance of a product in a particular application Symplex®. Given the variety of factors that can affect the use and performance of a product, the user is solely responsible for evaluating the Symplex® product and determine whether it is fit for a particular purpose and suitable for the method of application.

### HOW TO USE

- 

Shake well to activate the Polymers
- 

Using a wax applicator put a small quantity
- 

Can be use in all exterior of the vehicle
- 

Let it dry for at least 2 minutes
- 

Remove with a clean Microfiber cloth
- 

Not intended to be use inside the vehicle