

# TECHNICAL SPECIFICATIONS

## G5 PASTEWAX & SEALANT

REFERENCE I43-0004



### DESCRIPTION

**Symplex® G5 Paste Wax & Sealant.** Ultra Gloss long lasting Synthetic Protection, easy to apply and remove. Can be use in all kind of Paint, Stainless Steel, Chrome and Aluminum. Does not leave any white residue on plastic trims.

### PHYSICAL PROPERTIES

- Purple colored paste.
- Snap cap.
- It is applied by hand or with Tassel foam.
- Does not stain the plastic exterior parts.

### APPLICATION TECHNIQUES

The G5®, Ultra brightness was designed to facilitate and improve the quality of both enlisted vehicle paint shops and dealers.

- If applied manually, use a small amount in a special applicator Symplex P / N 111-0029 - UN or a micro-fiber cloth and lightly rub in a circular motion.
- Let dry approx. 60 seconds and remove with a clean cloth.

- For application with polishing machine , use a puff or foam pad Symplex Turbo P / N 133-0007 - A place a small amount and buff at low speed approx. 1200 rpm.

### CONTAINERS

10 oz. They are made of high density polyethylene (HDPE).

It also provides a snap cap in order to facilitate the closure of the container , preventing contamination and drying of the product and allow reopening accurately and easily.

### SPEED POLISHER / DA POLISHER

Most polishing machines found in workshops repair both electrical and neumatic can be used with the Symplex® G5. A rotational speed between 1000 and 1200 rpm is recommended

### BUFFING & FINISHING PAD

In case of preferring apply G5® with a polishing machine, you can use it with a Symplex Turbo Foam Pad P/N 133-0007-UN with a rotational speed of 1200 rpm.

### HANDLING AND STORAGE

See the Safety Data Sheet (MSDS)

### PREVENTIVE INFORMATION

See product label and Material Safety Data Sheet for health and safety information before using this product.

### WARRANTY AND LIMITATION OF RESOURCES

Technical Information: The technical information, recommendations, and other statements contained in this document are based upon tests or experience that Symplex® considered reliable, but the accuracy of such information or exhaustive is not guaranteed.

Product Use: Many factors beyond the control of Symplex® and only the user's knowledge and control can affect the use and performance of a product in a particular application Symplex®. Given the variety of factors that can affect the use and performance of a product, the user is solely responsible for evaluating the Symplex® product and determine whether it is fit for a particular purpose and suitable for the method of application.

### HOW TO USE

