

TECHNICAL SPECIFICATIONS



ULTRA WAX UP3

REFERENCE: 143-0002



Sizes:

Gallons - Quarts - Pints - 8 oz
3.748 ml. 948 ml. 473 ml. 236 ml.

DESCRIPTION

Symplex® Ultra Wax UP3, Professional Premium Carnauba Wax with long lasting Resin. This creamy formula will leave a thick film on paint with outstanding deep gloss and protection. The use of durable resin extends the life of the Carnauba. Easy to apply and remove. No white residue on black molding. Can be use in all kind of Paint, Stainless Steel, Chrome and Aluminum. Ultra Wax UP3, offers maximum UV protection to keep your vehicle's paint looking great for years. Detergent resistant polymers. Works exceptionally well on black and red paint. Spreads evenly leaving a clean, wet look finish. Recommended for clear coats. Use by hand or orbital polisher.

PHYSICAL PROPERTIES

- Purple colored
- Liquid Viscous
- Product Shell Lif: 2 years

APPLICATION TECHNIQUES

The Symplex® Ultra Wax UP3, was designed to improve the quality of Detailing centers, Dealerships and Body Shop.

SHAKE WELL BEFORE USING

- If applied manually, use a small amount in a special applicator Symplex P / N 111-0029 - UN or a microfiber cloth and lightly rub in a circular motion.
- Let dry approx. 2 minutes and remove with a clean cloth.
- For application with polishing machine , use a Symplex's special gloss foam pads - place a small amount and buff at low speed approx. 1500 rpm .

CONTAINERS

8 oz containers. 16 oz. 32 oz. They are made of high strength PET . 128 oz container.(Gallon) is produced in high density polyethylene (HDPE) It also provides a metering plastic cap in order to facilitate the closure of the container, preventing contamination, drying of the product, permit reopening, accurate and simple dosing.

SPEED POLISHER / DA POLISHER

Most polishing machines found in workshops repair both electrical and pneumatic can be used with the Symplex® Ultra Wax UP3. A rotational speed between 1500 and 2000 rpm is recommended

FINISHING PAD

Use Symplex® Ultra Wax UP3 with our following premium pads, Extreme Foam Pad P/N 133-0007-UN, Euro Foam XG Gloss Black P/N 133-0014-UN

HANDLING AND STORAGE

See the Safety Data Sheet (MSDS)

PREVENTIVE INFORMATION

See product label and Material Safety Data Sheet for health and safety information before using this product.

WARRANTY AND LIMITATION OF RESOURCES

Technical Information: The technical information, recommendations, and other statements contained in this document are based upon tests or experience that Symplex® considered reliable, but the accuracy of such information or exhaustive is not guaranteed.

Product Use: Many factors beyond the control of Symplex® and only the user's knowledge and control can affect the use and performance of a product in a particular application Symplex®. Given the variety of factors that can affect the use and performance of a product, the user is solely responsible for evaluating the Symplex® product and determine whether it is fit for a particular purpose and suitable for the method of application.

HOW TO USE

 <p>1</p>	 <p>2</p>	 <p>3</p>
Shake well to activate the Polymers	Using a wax applicator put a small quantity	Can be use in all exterior of the vehicle
 <p>4</p>	 <p>5</p>	 <p>6</p>
Let it dry for at least 2 minutes	Remove with a clean Microfiber cloth	Not intended to be use inside the vehicle