

TECHNICAL SPECIFICATIONS

PLASTI-K EXTERNAL

REFERENCE: 151-0004



Sizes:
Gallons - Quarts - Pints - 8 oz
3.748 ml. 948 ml. 473 ml. 236 ml.

DESCRIPTION

Plasti-K Xtreme Exterior Pro Dressing, Long lasting Professional molding and trim revival dressing. With UV blockers produce a satin OEM gloss dry to the touch non sticky surface. Last for weeks and withstands washing / rain. Can be use in any plastic color. For Interior Vinyl and Plastic trim use our exclusive "Non Silicone Internal Plasti-K Xtreme Pro Dressing"

NON STICKY FORMULA

PHYSICAL PROPERTIES

- Gray colored liquid cream.
- Container with metered plastic cap.
- It is applied by hand.
- Product life : 1 year.

APPLICATION TECHNIQUES

By using the Plasti-K® External may significantly improve and protect the appearance of the whole vehicle external plastic parts.

SHAKE WELL BEFORE USING.

- Use a small amount on a microfiber cloth spread evenly over the clean, dry surface, if necessary reapply the product.
- The Plasti-k® dry in about 5 minutes, no need to be removed.
- For better hydration, protection and durability with our cleaner clean SOLOFIX® Multi Use all leather surfaces before applying Plasti-k®.

CONTAINERS

8 oz containers. 16 oz. 32 oz. They are made of high strength PET . 128 oz container. (MPG) is produced in high density polyethylene (HDPE) It also provides a metering plastic cap in order to facilitate the closure of the container, preventing contamination, drying of the product, permit reopening, accuracte and simple dosing.

HANDLING AND STORAGE

See the Safety Data Sheet (MSDS)

PREVENTIVE INFORMATION

See product label and Material Safety Data Sheet for health and safety information before using this product.

WARRANTY AND LIMITATION OF RESOURCES

Technical Information: The technical information, recommendations, and other statements contained inthis document are based upon tests or experience that Symplex® considered reliable, but the accuracy of such information or exhaustive is not guaranteed.

Product Use: Many factors beyond the control of Symplex® and only the user's knowledge and control can affect the use and performance of a product in a particular application Symplex®. Given the variety of factors that can affect the use and performance of a product, the user is solely responsible for evaluating the Symplex® product and determine whether it is fit for a particular purpose and suitable for the method of application.

HOW TO USE





Using an clean applicator spread the product evenly reapply if necessary



Let it dry for at least 5 minutes

