

TECHNICAL SPECIFICATIONS

SILEX CERAMIC TRIM

REFERENCE: 161-0002



Sizes: Gallons - Quarts - Pints - 8 oz 3.748 ml. 948 ml. 473 ml. 236 ml.

DESCRIPTION

Symplex® Ceramic Trim Dressing, Professional water based Quartz treatment for all fessional water based Quartz treatment for all interior and exterior plastic trim. Unique satin OEM gloss, dry to the touch non-sticking formula. Providing an hidrophobic long lasting protection while maintain a like-new OEM appearance. Contains the latest SiO2 Silica Technology. Silex Ceramic Trim incorporates the durability and hardness of glass in an easy to apply creamy formula, outperforming regular silicone dressing. Our formula is made with Ceramic Silica Technology that leaves a Non-Stiicky surface with OEM appearance and extremely hydrophobic, lasting for 3-6 months!

PHYSICAL PROPERTIES

- Physical state: Liquid cream
- Cólor: Light gray Odor: Fruity
- Shelf Life: 2 years

APPLICATION TECHNIQUES

By using the Silex® Ceramic Trim, may significantly improve and protect the appearance of the whole vehicle external plastic trim parts.

SHAKE WELL BEFORE USING.

- Use a small amount on clean applicator spread evenly over the clean, dry surface, if necessary reapply the product.
- Let it dry for about 5 minutes, no need to be removed.
- In order to improve the protection and durability of the Silex Ceramic Trim is really importand to clean deeply the surface.

CONTAINERS

8 oz. - 16 oz. - 32 oz. bottles are made of high strength PET . 128 oz. (Gallon) is produced in high density polyethylene (HDPE)

It also provides a metering plastic cap in order to facilitate the closure of the container, preventing contamination, drying of the product, permit reopening, accuracte and simple dosing.

HANDLING AND STORAGE

See the Safety Data Sheet (MSDS)

PREVENTIVE INFORMATION

See product label and Material Safety Data Sheet for health and safety information before using this product.

WARRANTY AND LIMITATION OF RESOURCES

Technical Information: The technical information, recommendations, and other statements contained inthis document are based upon tests or experience that Symplex® considered reliable, but the accuracy of such information or exhaustive is not guaranteed.

Product Use: Many factors beyond the control of Symplex® and only the user's knowledge and control can affect the use and performance of a product in a particular application Symple-x®. Given the variety of factors that can affect the use and performance of a product, the user is solely responsible for evaluating the Symplex® product and determine whether it is fit for a particular purpose and suitable for the method of application.

HOW TO USE





Using an clean applicator spread the product evenly reapply if necessary



Let it dry for at least 5 minutes

