

TECHNICAL SPECIFICATIONS



BACKING PLATE FLEX 6"

REFERENCE	PRODUCT DESCRIPTION	UN/BOX	ANCHOR TYPE
132-0004-UN	BACKING PLATE	12	THREAD 5/8
132-0005-UN	BACKING PLATE	12	THREAD 14 mm

DESCRIPTION

The FLEX support pads or Velcro type fastening Berets , has a diameter of 6 inches which gives you great flexibility both Berets foam as Lana ,being able to fit the contours of the curves Vehicle parts and prevent damage the painting. The PAD Double Face Extreme is compatible with all types of paint (polyester, polyurethane , enamels , lacquers , etc.) .

FEATURES

- 6 " inches in diameter.
- 5/8 threads 14 mm for fleas and European machines .
- Compatible with all Pads or VELCRO type attachment Berets

- High Performance and Durability
- Excellent Flexibility

APPLICATIONS

Because of its excellent flexibility is ideal for use with all types of pads or Velcro-type fastening Berets .

INSTRUCTIONS

- The rotational speed must not exceed 3500 rpm.
- Check that you have correctly threaded support in the polishing machine.
- Use proper thread 5/8 inch machines and 14 mm American type . For European type polishing machines .

PRECAUTIONS

- Keep away from sources of ignition

- Wear safety glasses
- Use hearing protection

WARRANTY AND LIMITATION OF RESOURCES

Technical Information: The technical information, recommendations, and other statements contained in this document are based upon tests or experience that Symplex® considered reliable, but the accuracy of such information or exhaustive is not guaranteed.

Product Use: Many factors beyond the control of Symplex® and only the user's knowledge and control can affect the use and performance of a product in a particular application Symplex®. Given the variety of factors that can affect the use and performance of a product, the user is solely responsible for evaluating the Symplex® product and determine whether it is fit for a particular purpose and suitable for the method of application.