



TECHNICAL SPECIFICATIONS

MARINE BOAT PRO WAX

REFERENCE: 172-0001

	Sizes:			
	Gallons	Quarts	Pints	8 oz
	3.784 ml.	948 ml.	473 ml.	236 ml.

DESCRIPTION

Symplex® Boat Pro Wax, Professional Premium Synthetic Sealant + Carnauba Wax. This creamy formula will leave a thick film on fiberglass, Gel-Coat, Metal and painted surfaces with outstanding deep gloss and protection. The use of durable synthetic sealant extends the life of the Carnauba. Easy to apply and remove. No white residue on black molding and trims. Clear coat safe.

GEL - COAT METAL & PAINTED SURFACES SYNTHETIC + CARNAUBA WAX

An easy to use VOC compliant blend of carnauba wax and detergent resistant synthetic polymers. Works exceptionally well on dark colors boats. Spreads evenly leaving a clean, wet look finish. Recommended for fiberglass and clear coats. Use by hand or orbital polisher.

PHYSICAL PROPERTIES

- White color
- Liquid (viscous)
- Odor Fruity
- VOC compliant
- Containers with metered plastic lids.
- Product life: 1 year.

APPLICATION TECHNIQUES

- The Symplex® Boat Pro Wax, should be applied to a clean unoxidized surfaces. For hand use: Apply with a clean soft cloth using a circular motion. Allow to dry to a haze. Buff to a high gloss using a soft clean dry cloth.

- For orbital polisher apply wax to clean bonnet. With orbital on, spread over surfaces. Allow to dry to a haze. With clean bonnet, buff to a high gloss.

SHAKE WELL BEFORE USING.

CONTAINERS

8 oz containers. 16 oz. 32 oz. They are made of high strength PET . 128 oz container. (MPG) is produced in high density polyethylene (HDPE) It also provides a metering plastic cap in order to facilitate the closure of the container, preventing contamination, drying of the product, permit reopening, accurate and simple dosing.

HANDLING AND STORAGE

See the Safety Data Sheet (MSDS)

PREVENTIVE INFORMATION

See product label and Material Safety Data Sheet for health and safety information before using this product.

WARRANTY AND LIMITATION OF RESOURCES

Technical Information: The technical information, recommendations, and other statements contained in this document are based upon tests or experience that Symplex® considered reliable, but the accuracy of such information or exhaustive is not guaranteed.


HOW TO USE / MODO DE EMPLEO



Shake well to activate
Agítese bien para activar



Apply using a Wax applicator
Utilice un aplicador o paño limpio



Let it dry at least for 2 minutes
Deje secar mínimo por 2 minutos



Remove using a microfiber cloth
Retire con un paño de Microfibra

