

TECHNICAL SPECIFICATIONS

SILEX REACTIVE PASTE SEALANT

REFERENCE: 161-0004-10W

 Sizes:
10 oz
296 ml.

DESCRIPTION

Silex Silazane Infused Ceramic Protection Sealant, Professional treatment will impart a hydrophobic glossy protecting coating layer that outperforms any conventional paste Carnauba wax or sealant. Infused with Organic Polysilazane polymers that will transform into dense ceramic-like layers upon curing.

- Perfect for use as a stand-alone protection.
- Symplex® Cross-Link technology that full cures in 24H
- User-Friendly application - Easy to apply and removal
- 100% Synthetic
- Detergent resistance

PHYSICAL PROPERTIES

- Red colored
- Container with sponge applicator
- Product life : 1 year.

APPLICATION TECHNIQUES

Silex Reactive Paste Sealant is an user-friendly that can be used as a stand alone sealant or as a maintenance over our Silex Ceramic Coating 9H.

HAND APPLICATION

- 1- Using the premium foam applicator (included)
- 2- Apply a small amount onto the foam pad and buff using circular motions, working on one section at a time.
- 3 - Let it dry for at least 5 minute to ensure the best bonding time.
- 4- Use a clean, soft microfiber cloth to gentle wipe over and buff, checking reflections and gaps from all angles to ensure you have removed every last trace of product.

DA ORBITAL POLISHER

Electric or pneumatic DA Orbytal buffer machines can be used to apply Symplex Silex Reactive Paste Sealant. We recommend use our Euro Foam XG Gloss finishing Pad.

CONTAINERS

10 oz. made of high density polyethylene (HDPE). with screw type lid

Screw type lid facilitate the closure of the container , preventing contamination and drying of the product and allow reopening accurately and easily.

HANDLING AND STORAGE

See the Safety Data Sheet (SDS)

PREVENTIVE INFORMATION




See product label and Material Safety Data Sheet for health and safety information before using this product.

WARRANTY AND LIMITATION OF RESOURCES

Technical Information: The technical information, recommendations, and other statements contained inthis document are based upon tests or experience that Symplex® considered reliable, but the accuracy of such information or exhaustive is not guaranteed.

Product Use: Many factors beyond the control of Symplex® and only the user's knowledge and control can affect the use and performance of a product in a particular application Symplex®. Given the variety of factors that can affect the use and performance of a product, the user is solely responsible for evaluating the Symplex® product and determine whether it is fit for a particular purpose and suitable for the method of application.

HOW TO USE

-  1 Using an applicator put a small quantity
-  2 Using a circular movement apply a medium coat evenly.
-  3 Let it dry between 5-10 minutes, then remove using a dry microfiber cloth.

