



## Rhino Automotive

Sizes: Gallon 128 US.Fl. Oz. - 3.785 ml  
 Quart 32 US.Fl. Oz. - 948 ml

### Rubbing Compound

PART NUMBER: RRC-01-4

#### DESCRIPTION

**Rhino Rubbing Compound**, Professional abrasive compound. Removes 1200 grit sand scratches, oxidation, and water spots. A quick cutting, fast acting compound. High gloss and very little surface swirling. To increase the gloss and eliminate compounding swirl marks use **Rhino Machine Glaze Step 2**. Great for all types of painted substrates. Easy to clean up.

**NO SILICONE**  
**NO FILLERS**  
**BODY SHOP SAFE**

Professional Heavy Duty Rubbing Compound corrects the worst paint imperfections to set the stage for a smooth, flawless finish. This compound removes heavy imperfection, 1200 grit scratches, and swirls with a professional grade formula. The Rhino Rubbing Compound generates very low dust, it is easy to remove, does not stain plastic parts, increases productivity.

Safe to be used on the latest generation of Paint

#### PHYSICAL PROPERTIES

- Beige colored cream
- Odor Characteristic
- Containers with metered plastic lids.
- Recommended application rate: 1500-2000 rpm.
- Product life: 1 year.

#### APPLICATION TECHNIQUES

Rhino Rubbing Compound can be applied with any type of polisher – rotary or dual action – with foam, wool or microfiber pads.

SHAKE WELL BEFORE USING.

Use Rhino Rubbing Compound with a wool or foam compounding pad, with a rotary polisher apply a medium pressure at 1500-1800 rpm. with DA polisher use at medium to high speed with overlapping passes. When the sanding scratches or imperfections have been removed, reduce pressure on the polisher. Use a microfiber towel to remove any residue from the paint. Follow up with **Rhino Machine Glaze** to obtain a high gloss flawless finish

#### CONTAINERS

32 oz. and 128 oz. containers are produced in high density polyethylene (HDPE) It also provides a metering plastic cap in order to facilitate the closure of the container, preventing contamination, drying of the product, permit reopening, accurate and simple dosing.

#### SPEED POLISHER / DA POLISHER

Most polishing machines found in Bodyshop or Detailing Center both electrical and pneumatic can be used with the Rhino Rubbing Compound.

#### HANDLING AND STORAGE

See the Safety Data Sheet (SDS) at [www.symplex.us](http://www.symplex.us)

#### PREVENTIVE INFORMATION

See product label and Safety Data Sheet (SDS) for health and safety information before using this product.

#### WARRANTY AND LIMITATION RESOURCES

##### Technical Information:

The technical information, recommendations, and other statements contained in this document are based upon tests or experience that Rhino Automotive considered reliable, but the accuracy of such information or exhaustively is not guaranteed.

##### Product Use:

Many factors beyond the control of Rhino Automotive and only the user's knowledge and control can affect the use and performance of a product in a particular application. Given the variety of factors that can affect the use and performance of a product, the user is solely responsible for evaluating the Rhino Automotive products and determine whether it is fit for a particular purpose and suitable for the method of application.

