

# Quarter-Turn Polyamide Pr20.1 L18

1-095



## Advantages

- For cutout Pr20.1.
- Protective insulated.
- IP65/67 according to DIN EN 60529 (optional).
- RH / LH application.
- The quarter-turn can be screwed into the cutout with the pre-assembled cam.
- When using inserts zinc die + cams stainless steel or inserts stainless steel + cams stainless steel, electrical continuity can be ensured by means of the grounding clip (f).

## Material

- **Housing and cams:** PA, black
- **Nut:** see table

## Remarks

(S) Door-thickness max. 8mm

Please configure the quarter-turn with insert and cam.  
Pre-assembling by DIRAK is advisable.

Slide shoe and MLA door contact only in conjunction with  
cams d1).

## Quarter-Turn housing + nut

	Product number	Version	Material nut	Installation type	Delivery Unit
a)	200-9003.00-00000	housing head frustoconical	steel	screw-on	10 pcs.
a)	200-9044.00-00000	housing head frustoconical	stainless steel	screw-on	10 pcs.
a)	200-9077.00-00000	housing head frustoconical	PA	screw-on	10 pcs.

	Product number	Version	Material nut	Installation type	Delivery Unit
b)	100-9611.00-00000	housing head rounded	steel	screw-on	10 pcs.
b)	100-9612.00-00000	housing head rounded	PA	screw-on	10 pcs.
b)	100-9614.00-00000	housing head rounded	stainless steel	screw-on	10 pcs.

Cams L35, with stop

	Product number	H-dimension	Delivery Unit
d)	200-5318.00-00000	18 mm	10 pcs.
d)	200-5320.00-00000	20 mm	10 pcs.
d)	200-5322.00-00000	22 mm	10 pcs.
d)	200-5325.00-00000	25 mm	10 pcs.
d)	200-5328.00-00000	28 mm	10 pcs.

