

Overview

The 14v 2200mAh rechargeable lithium battery from Wattnine is designed to provide high energy density.

Features

- · High energy density.
- · Equipped with Smart Battery Management System.
- · Long cycle life.
- · Excellent safty & performance.



Dimension and Weight



Charging/Discharging Connector





Battery Specification:

| Nominal Characteristics | |
|-----------------------------------|-------------------|
| Nominal Voltage /V | 14V |
| Nominal Capacity /Ah (25°C, 0.2C) | ≈2200mAh |
| Operating Voltage Range | 12.2V-16.8V |
| Pack Characteristics | |
| Design | 4S1F |
| Cell type/ Chemistry | 18650/ NMC |
| Mechanical Characteristics | |
| Weight | 160 gms |
| Dimensions (LxWxH) | 70 x 75 x 18 mm |
| Charging/Discharging Connector | DC Male Connector |
| Charging Characteristics | |
| Charge Voltage | 16.8V |
| Max. Continues Charge Current | 1.1 <i>A</i> |
| Charging Duration | ≈120Mins |
| Discharging Characteristics | |
| Max Voltage | 16.8V |
| Min Voltage | 12.2V |
| Max. Continues Discharge Current | 2.2A |

Page:1/2 www.wattnine.in







BMS - Battery Management System:

| Protection | | Range | Units |
|--------------------|------------------|-------------------------------|-------|
| Over Charge | Trigger Voltage | 4.25 | V |
| | Release Voltage | 4.05 | V |
| | Delay Time | 80 | ms |
| Over Discharge | Trigger Voltage | 2.40 | V |
| | Release Voltage | 3.0 | V |
| | Delay Time | 40 | ms |
| Over Current | Trigger Current | 23 | А |
| | Delay Time | 40 | ms |
| Balancing Function | NA | | |
| Short Circuit | Delay | 500 | μs |
| | Manual Reset | Connect Power Source to Reset | |
| Thermal Protection | High Temperature | NA | |
| | Low Temperature | NA | |

Page:2/2 www.wattnine.in