

Overview

The 12v 2600mAh rechargeable lithium ion battery from Wattnine is designed to provide high energy density for low-rate applications.

Features

- · High energy density.
- · Equipped with Smart Battery Management System.
- · Low self-discharge rate.
- · Long cycle life.
- · Excellent safty & performance.



DC Male Female Charging/Discharging Connector





Battery Specification:

Nominal Characteristics	
Nominal Voltage /V	11.1V
Nominal Capacity /Ah (25°C, 0.2C)	≈2600mAh
Operating Voltage Range	9.2V-12.8V
Pack Characteristics	
Design	3S1P
Cell type/ Chemistry	18650/ NMC
Mechanical Characteristics	
Weight	153 gms
Dimensions (LxWxH)	56 x 22 x 68 mm
Charging/Discharging Connector	DC Male Female Connector
Charging Characteristics	
Charge Voltage	12.8V
Max. Continues Charge Current	1.3A
Charging Duration	≈120Mins
Discharging Characteristics	
Max Voltage	12.8V
Min Voltage	9.2V
Max. Continues Discharge Current	2.6A

Page:1/2 www.wattnine.in







BMS - Battery Management System:

Protection		Range	Units
	Trigger Voltage	4.25	V
Over Charge	Release Voltage	4.05	V
	Delay Time	80	ms
Over Discharge	Trigger Voltage	2.40	V
	Release Voltage	3.0	٧
	Delay Time	40	ms
Over Current	Trigger Current	7	А
	Delay Time	40	ms
Balancing Function	NA		
Short Circuit	Delay	500	μs
	Manual Reset	Connect Power Source to Reset	
Thermal Protection	High Temperature	NA	
	Low Temperature	NA	

Page:2/2 www.wattnine.in