# **Technical Data Sheet**

261 Nail-Free Adhesive JUSTack



### **Product description**

MambaBond Nail-Free Adhesive with extremely adhesive force and bonding ability, is aimed to replace the metallic nail as general-purpose adhesive, and it doesn't require drilling holes for fixing and bonding materials such as wood, MDF board, gypsum, board, stone, concrete, ceramics, metal, plastic, rubber and so on.

## **Features and benefits**

Strong bonding property, high bonding strength High flexibility, bonding power not affected by shrink of building Wide application range, suitable for most of materials, even wet wood Suitable for filling gaps, cracks; Painting can be done after adhesive hardens Excellent weathering-resistance, water-proof property Non-toxic, no pollution, free of hazardous substances like benzene, formaldehyde. etc

## **Product data**

Appearance	Heavy paste, viscous liquid
Color	Ceramic white
Odor	Solvent with low odor
Viscosity	Approx.110,000 cps @ 25°C
Solids content	70± 2%
Specific gravity	1.3± 0.1 g/ml
Initial bonding strength	≥ 1.22 MPa.s
Tensile shear strength	≥ 3.0 MPa.s
Recommend heavy duty	30-35 kg
Flammability	Flammable
Chemical Resistance	Good
Application Temperature	-20 °C to + 50 °C
Initial Contact Time	3~10 minutes, depending on temp
Open Time	10~20 minutes, depending on temp
Maximum Bond	5~7 days depending on temp & thickness
Standard Package	360g / 300ml per tube

# **Technical Data Sheet**

261 Nail-Free Adhesive JUSTack



Storage & Packa	ge
Shelf Life	18 months in sealed cans
Storage	keep it out of touch of children; store it in a cool, dry
	and well-ventilated place. The storage temperature shall
	range 5 - 35 Celsius, and the relative humidity shall be
	<80%.
Packing size	300ml / 360g
	24 pieces in one carton

#### 0



**PIVOT Africa Materials (Pty) Ltd** 22 Magwa Crescent, Gateway West 1st Floor Waterval City, Johannesburg, Gauteng South Africa 2066

Last revised: Monday, September 30, 2019 NOT FOR PRODUCT SPECIFICATIONS. TECHNICAL DATA HEREIN ARE INTENDED FOR REFERENCE ONLY. PLEASE CONSULT OUR TECHNICAL SERVICE DEPARTMENT FOR ASSISTANCE AND RECOMMENDATIONS FOR YOUR SPECIFIC APPLICATION.